

9E6Ki

Eaton 9E6Ki 9e 6000i On-line UPS 6000VA 220-240V Tower

Product Overview

Eaton 9E6Ki 9e 6000i On-line UPS 6000VA 220-240V Tower, Pure Sine Wave Output Waveform, Online/Double-conversion, 15 batteries, Sealed lead-acid Battery Type



Specifications

Specifications:

© 2022 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	9E6Ki
General specifications	
Product Name	Eaton 9E UPS
Catalog Number	9E6KI
UPC	743172067661

ComX Computers

Product Specification Sheet

Product Length/Depth	61.29 cm
Product Height	70.85 cm
Product Width	26.24 cm
Product Weight	68 kg
Compliances	CE Marked
	TUV
Certifications	IEC/EN 62040-1
	IEC/EN 62040-2
	CE
	EAC
Product specifications	
Secondary frequency - max	60 Hz
Output waveform	Sine wave
Max number of battery packs	4
Wattage	4800 W
Output power factor	0.8
Form factor	Tower
Voltage distortion output (linear load) - max	3
Includes network card	No
Input connection	Hardwired/fixed connection
Input voltage - min	110 V
Output voltage - max	240 V
Secondary frequency - min	50 Hz
Software compatibility	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
Battery replacement	Replacable batteries
Battery type	Sealed, lead-acid
Efficiency	91
Number of outputs hardwired	1
Special features	Double conversion topology
	Constantly monitors power conditions and regulates voltage and frequency
	Internal bypass allows service continuity in case of UPS fault
	LCD display for real-time status and measurements
	Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)
	Long backup time with up to 4 optional EBM
Construction type	Free standing model
Output voltage - min	220 V

ComX Computers

Product Specification Sheet

Color	Black
Extended battery capability	Yes
Output voltage range	220/230/240 V +/- 2%
Topology	Online/Double-conversion
BTU Rating	Online: 1472
Efficiency (eco-mode)	96
Runtime at half load	10 min
Input nominal voltage	230V default (220/230/240V)
Input power factor	>.99
Input frequency range	45-66Hz
Internal bypass	Yes
Input voltage - max	276 V
Voltage type	AC
Phase (output)	1
Battery management	Automatic battery test
	Deep discharge protection
Auto shutdown function	Yes
VA rating	6000 VA
Potential free switch contact	Yes
Phase (input)	1
Package contents	UPS
	USB cable
	Serial cable
	User manual
Noise level	
Feed type	1
User interface	LCD Display
Battery quantity	15
Voltage	230V
Hot swap power	No
Temperature range	0 degrees to 40 degreesC (32 degrees to 104 degreesF)
Ethernet interface	No
Communication	USB port (HID compliant)
	Serial port (RS232)
	Mini-terminal block for remote power off
	Communication slot
Relative humidity	0-95% non-condensing

ComX Computers

Product Specification Sheet

Rack mounting kit	No
Output frequency	50/60 Hz
Runtime at full load	8 min
Type of interface	Other
Primary frequency - min	45 Hz
Battery rating	12 V / 9 Ah
Type	UPS
Output nominal voltage	230V default (220/230/240V)
Expansion slots	One slot for optional communication card
Input voltage range	176-276 V (110-276 V with derating)
Nominal frequency	50/60 Hz
Primary frequency - max	66 Hz
Altitude	3000 m

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/9E6Ki-Eaton-9E6Ki-9e-6000i-On-line-UPS-6000VA-220-240V-Buy-p-272805.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-23 19:11:36.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.