
ComX Computers
Product Specification Sheet

ARCHER-T600U-NANO

TP-Link Archer T600U Nano AC600 Nano Wi-Fi USB Adapter

Product Overview

TP-Link Archer T600U Nano AC600 Nano Wi-Fi USB Adapter, 433Mbps at 5GHz + 200Mbps at 2.4GHz, USB 2.0



Specifications

Features:

- High Speed WiFi- Up to 600Mbps speeds with 200Mbps on 2.4GHz and 433 Mbps on 5GHz, upgrades your devices to higher AC WiFi speeds.
- Dual Band Wireless - 2.4GHz and 5GHz band for flexible connectivity, upgrades your devices to work with the latest dual-band WiFi router for faster speed and extended range.
- Nano design - Small, unobtrusive design allows you to plug it in and forget it is even there
- Operating System - Supports Windows 10/8.1/8/7/XP, Mac OS X
- Advanced Security -Supports 64/128-bit WEP, WPA/WPA2, and WPA-PSK/WPA2-PSK encryption standards

High-Speed Dual Band Adapter for Better Connections
The Archer T600U Nano receives Wi-Fi signals on two separate bands. Supporting 256QAM technology increases 2.4GHz data rate from 150Mbps to 200Mbps for 33% faster performance.433Mbps on 5GHz is ideal for HD video streaming and lag-free online gaming, while 200Mbps on 2.4GHz is perfect for normal use such as web surfing with legacy devices.

Miniature Design Plug in and forget
With its miniature size and sleek design, users can insert the nano adapter into any USB port and leave it there, no matter when they are traveling or at home.

Travel size and Wi-Fi Roaming Great Choice for mobile surfing
Growing public Wi-Fi services comes with one inconvenience - you might have to repeatedly select and connect to different Wi-Fi networks while moving. Archer T600U Nano supports Wi-Fi Roaming that helps your devices connect to the most suitable Wi-Fi automatically as you move, ensure your network is uninterrupted, and with its small, travel-size, Archer T600U Nano is undoubtedly a great choice for mobile surfing.

Easy Setup
A friendly user interface for simple installation.

Advanced Security

WPA/WPA2 encryption standards ensure your wireless connection is safe from intruders.

Operating System

Supports operating systems include Windows 10/8.1/8/7/Vista/XP, Mac OS.

Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	ARCHER-T600U-NANO
HARDWARE FEATURES	
Interface	USB 2.0
Dimensions (W x D x H)	15*7.1*18.6mm
Antenna Type	Omni Directional
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11ac, IEEE 802.11a
	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency	5GHz
	2.4GHz
Signal Rate	5GHz
	11ac: Up to 433Mbps(dynamic)
	11n: Up to 150Mbps(dynamic)
	11a: Up to 54Mbps(dynamic)
	2.4GHz
	11n: Up to 200Mbps(dynamic)
	11g: Up to 54Mbps(dynamic)
	11b: Up to 11Mbps(dynamic)

Reception Sensitivity	5GHz :
	11a 6Mbps: -90dBm
	11a 54Mbps: -73dBm
	11n HT20 MCS0: -89dBm
	11n HT20 MCS7: -70dBm
	11n HT40 MCS0: -86dBm
	11n HT40 MCS7: -67dBm
	11ac VHT80 MCS0: -82dBm
	11ac VHT80 MCS9: -56dBm
	2.4GHz:
	11b 1Mbps: -96dBm
	11b 11Mbps: -88dBm
	11g 6Mbps: -89dBm
	11g 54Mbps: -74dBm
	11n HT20 MCS0: -89dBm
	11n HT20 MCS7: -72dBm
	11n HT40 MCS0: -86dBm
	11n HT40 MCS7: -66dBm
Transmit Power	
Wireless Modes	Ad-Hoc / Infrastructure mode
Wireless Security	Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Modulation Technology	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	AC600 Nano Wireless USB Adapter Archer T2U Nano
	Resource CD
	Quick Installation Guide
System Requirements	Windows 10/8.1/8/7/XP (32/64bits)
	Mac OS X 10.9-10.13
Environment	Operating Temperature: 0 degreesC~40 degreesC (32 degreesF~104 degreesF)
	Storage Temperature: -40 degreesC~70 degreesC (-40 degreesF~158 degreesF)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx.co.za/ARCHER-T600U-NANO-TP-Link-Archer-T600U-Nano-AC600-Nano-Wi-Fi-USB-Adapter-p-286511.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx.co.za/terms-of-use.php
Terms of Sale: https://www.comx.co.za/terms-of-sale.php

PDF generated: 2026-11-19 17:40:34.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.