

DS-2CE16D0T-EXIPF2.8MM

Hikvision 2MP fixed Mini Bullet analogue camera with 2.8mm Lens

Product Overview

Hikvision 2MP fixed Mini Bullet Analogue Camera with 2.8mm Lens, 2 MP CMOS image sensor, PAL / NTSC signal system, 1920 (H) x 1080 (V) Resolution, M12 Lens Mount, AGC, BLC, Global, DWDR, 2D DNR noise reduction, Switchable TVI / AHD / CVI / CVBS Video Output, Up to 20m IR range



Specifications

Overview:

DS-2CE16D0T-EXIPF - 2 MP Fixed Mini Bullet Camera

- High quality imaging with 2 MP, 1920 x 1080 resolution
- 2.8 mm, 3.6 mm fixed lens
- Up to 20 m IR distance for bright night imaging
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP66)

Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	DS-2CE16D0T-EXIPF2.8MM
Camera	
Model	DS-2CE16D0T-EXIPF
Product Name	2MP Outdoor EXIR Fixed Mini Bullet Camera
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) x 1080 (V)

ComX Computers

Product Specification Sheet

Frame Rate	TVI: 1080p@25fps/30fps
	AHD: 1080p@25fps/30fps
	CVI: 1080p@25fps/30fps
	CVBS: PAL/NTSC
Min. Illumination	0.02 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1 / / / 50,000 s, NTSC: 1/30 s to 1 / / / 50,000 s
Lens	2.8 mm, 3.6 mm Fixed Lens
Field of View	2.8 mm, horizontal FOV: 96.5 degrees, vertical FOV: 48.9 degrees, diagonal FOV: 120.5 degrees
	3.6 mm, horizontal FOV: 76.9 degrees, vertical FOV: 40.6 degrees, diagonal FOV: 92.0 degrees
Lens Mount	M12
Day & Night	IR Cut Filter
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0 degrees to 360 degrees, Tilt: 0 degrees to 90 degrees, Rotation: 0 degrees to 360 degrees
Image	
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	Auto
AE (Auto Exposure) Mode	BLC, Global, DWDR
Noise Reduction	2D DNR
Language	English
Function	Sharpness, Smart IR, Mirror, Brightness
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40 degreesC to 60 degreesC (-40 degreesF to 140 degreesF), Humidity: 90% or less (non-condensing)
Power Supply	12 VDC +/- 25%
Consumption	Max. 3.3 W
Protection Level	IP66
Material	Plastic
IR Range	Up to 20 m
Communication	HIKVISION-C
Dimension	138.8 mm x 60.9 mm x 57.9 mm (5.465" x 2.389" 2.278")
	Approx. 145 g (0.32 lb.)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/DS-2CE16D0T-EXIPF2-8MM-Hikvision-2MP-fixed-Mini-Bullet-Buy-p-283770.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-11 04:49:36.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.