

DS-2CE70DF0T-LMFS-2.8MM

Hikvision DS-2CE70DF0T-LMFS 2 MP Smart Hybrid Light with ColorVu Fixed Turret Camera with 2.8mm Lens

Product Overview

Hikvision DS-2CE70DF0T-LMFS 2 MP Smart Hybrid Light with ColorVu Fixed Turret Camera with 2.8mm Lens



Specifications

Features:

- High quality imaging with 2 MP, 1920 x 1080 resolution
- 24/7 color imaging with F1.0 aperture
- Smart-Hybrid light, optimize your security with flexible lighting options
- 3D DNR technology delivers clean and sharp images
- 2.8 mm, 3.6 mm fixed focal lens
- Up to 20 m white light distance for bright night imaging
- High quality audio with audio over coaxial cable, built-in mic
- Up to 20 m IR distance for bright night imaging
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)

Specifications:

© 2025 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	DS-2CE70DF0T-LMFS-2.8MM
Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) x 1080 (V)
Min. Illumination	0.001 Lux @ (F1.0, AGC ON), 0 Lux with white light

ComX Computers

Product Specification Sheet

Shutter Time	PAL: 1/25 s to 1/50, 000 s; NTSC: 1/30 s to 1/50, 000 s
Day & Night	ICR
Angle Adjustment	Pan: 0 degrees to 360 degrees, Tilt: 0 degrees to 75 degrees, Rotate: 0 degrees to 360 degrees
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm fixed focal lens
Focal Length & FOV	2.8 mm, horizontal FOV: 105 degrees, vertical FOV: 56 degrees, diagonal FOV: 126 degrees
Lens Mount	M12
Microphone	
Pickup Distance	In a radius of up to 5 m
Amount	1
Illuminator	
Supplement Light Type	Smart, IR, White Light
Supplement Light Range	IR: Up to 20 m, White Light: Up to 20 m
Image	
Image Parameters Switch	STD/HIGH-SAT/HIGHLIGHT
Image Settings	Brightness, Sharpness, Anti-banding, AGC
Frame Rate	TVI: 1080p @25 fps/30 fps
	CVI: 1080p @25 fps/30 fps
	AHD: 1080p @25 fps/30 fps
	CVBS: PAL/NTSC
Day/Night Mode	Auto/Color
Wide Dynamic Range (WDR)	Digital WDR
Noise Reduction	3D DNR/2D DNR
Image Enhancement	DWDR
	BLC
	HLC
	Global
White Balance	Auto, Manual
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Material	Metal
Power	12 VDC +/- 25%, max. 2.9 W, *You are recommended to use one power adapter to supply the power for one camera.
Dimension	Ø85.11 mm x 77.62 mm (Ø3.35" x 3.05")

ComX Computers

Product Specification Sheet

Weight	Approx. 320 g (0.71 lb.)
Operating Condition	-40 degreesC to 60 degreesC (-40 degreesF to 140 degreesF). Humidity 90% or less (non-condensing)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/DS-2CE70DF0T-LMFS-2-8MM-Hikvision-DS-2CE70DF0T-LMFS-Buy-p-317935.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-09 07:29:48.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.