

DS-2XM6726FWD-I

Hikvision DS-2XM6726FWD-I Mobile Network IP camera 2MP

Product Overview

Hikvision DS-2XM6726FWD-I Mobile Network IP camera 2MP, 1/2.8" Progressive Scan CMOS image sensor, 3D DNR, 120 dB WDR, M12 Lens Mount, 1920x1080 Maximum Resolution, H.265/H.264 main stream Video, 1x RJ45 10M/100M Ethernet Port



Specifications

Overview:

Mobile Mini Dome network Camera

- High quality imaging with 2 MP resolution
- Efficient H.265+ compression technology
- Clear imaging against strong back light due to 120 dB WDR technology

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	DS-2XM6726FWD-I
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.005 Lux @ (F1.2, AGC ON), 0.009 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100, 000 s
Slow Shutter	Yes
Angle Adjustment	Pan: -30 degrees to +30 degrees, Tilt: 0 degrees to 75 degrees, Rotate: 0 degrees to 360 degrees
Digital Noise Reduction	3D DNR
WDR	120 dB

ComX Computers

Product Specification Sheet

Day & Night	IR Cut Filter
Lens	
Auto-Iris	No
Aperture	F1.6
FOV	2.0 mm @ F1.6, horizontal FOV 132 degrees, vertical FOV 77 degrees, diagonal FOV 153 degrees, 2.8 mm @ F1.6, horizontal FOV 110 degrees, vertical FOV 60 degrees, diagonal FOV 130 degrees, 4 mm @ F1.6, horizontal FOV 82 degrees, vertical FOV 45 degrees, diagonal FOV 98 degrees, 6 mm @ F1.6, horizontal FOV 56 degrees, vertical FOV 31 degrees, diagonal FOV 65 degrees, 8 mm @ F1.6, horizontal FOV 40 degrees, vertical FOV 22 degrees, diagonal FOV 46 degrees
Lens Mount	M12
Focal length	2.0/2.8/4/6/8 mm fixed lens
Video	
Max. Resolution	1920 x 1080
Main Stream	H.265/H.264
Sub Stream	H.265/H.264/MJPEG
Third Stream	H.265/H.264
Video Compression	Main stream: H.265/H.264, Sub-stream: H.265/H.264/MJPEG, Third stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.265 Type	Main Profile
Video Bit Rate	32 Kbps to 16 Mbps
SVC	H.264 and H.265 encoding
Audio	
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio Bit Rate	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-192Kbps(MP2L2)
Environment Noise Filtering	Yes
Audio Sampling Rate	8kHz/16kHz/32kHz/44.1kHz/48kHz
Smart Feature-Set	
Behavior Analysis	Line crossing detection, intrusion detection, unattended baggage detection, object removal detection
Region of Interest	1 fixed region for main stream and sub stream
Image	
Image Enhancement	BLC, 3D DNR
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser
Target Cropping	No
Day/Night Switch	Day/Night/Auto/Schedule/Triggered by Alarm In (-S)
Picture Overlay	No
Network	

ComX Computers

Product Specification Sheet

Network Storage	Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS, SMB/CIFS), ANR
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users,3 levels: Administrator, Operator and User
Client	iVMS-4200, iVMS-4500, iVMS-5200, Hik-Connect
Web Browser	IE8+, Chrome31.0-44, Firefox30.0-51, Safari8.0+
Alarm Trigger	Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet port
Reset Button	Yes
Audio (-S)	1 input (line in), 1 built-in mic, 1 output (line out), mono sound
Alarm (-S)	1 input, 1 output (up to 12VDC, 30mA)
On-board storage	Built-in micro SD/SDHC/SDXC slot, up to 128 GB
Compression Standard	
H.264+	Main stream support.
H.265+	Main stream support.
Smart Feature-Set	
Face Detection	Yes
Exception Detection	No
General	
Firmware Version	V5.5.4
General Function	One-key reset, anti-flicker, three streams, heartbeat, password protection, privacy mask, watermark, IP address filter
Power Supply	-I, -IS: 12 VDC +/- 25%, 5.5 mm coaxial power plug, -IM: 12 VDC +/- 25%, Molex plug for DC input, PoE (802.3af, class 3)
Power Consumption and Current	12 V DC +/- 25%, 0.5 A, max. 6 W, PoE: (802.3af, 36V-57V), 0.2A to 0.13A, Max:7.5W
Material	Metal
Dimensions	Camera: Ø 110 mm x 57.4 mm (4.3" x 2.26"), with base: Ø 110 mm x 69.4 mm (4.3" x 2.7") With package: 252 mm x 160 mm x 95 mm (9.9" x 6.3" x 3.7")
	Camera: Approx. 580 g (1.3 lb.), With package: 860 g (1.9 lb)
Operating Conditions	-30 degreesC to 60 degreesC (-22 degreesF to 140 degreesF), humidity less than 95% or less (non-condensing)
Protection Level	IP67, IK10

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx.co.za/DS-2XM6726FWD-I-Hikvision-DS-2XM6726FWD-I-Mobile-Network-IP-camera-2MP-p-256023.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-27 19:35:16.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.