

DS-9632NXI-I8/S

Hikvision AcuSense 32 channel 2U 4K AcuSense NVR

Product Overview

Hikvision AcuSense 32 channel 2U 4K AcuSense NVR, H.265+ / H.265 / H.264+ / H.264 Video formats, Up to 32-ch IP camera inputs, Up to 16-ch 1080p decoding capability, Up to 1-ch facial recognition for Video Stream, 1-ch Two-Way audio, 2x RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface, 8x SATA interfaces, Up to 10 TB capacity for each disk, RS-485 (Full-Duplex), RS-232, Keyboard, 2x USB 2.0, 1x USB 3.0, 16 / 8 alarm In/Out



Specifications

Overview:

32-ch 2U 4K AcuSense NVR

- H.265+/H.265/H.264+/H.264 video formats
- Intelligent analytics based on deep learning algorithm
- Up to 4-ch perimeter protection
- Up to 1-ch facial recognition for video stream, or up to 4-ch facial recognition for face picture
- Up to 32-ch IP camera inputs
- Up to 16-ch 1080p decoding capability
- Up to 320 Mbps incoming bandwidth

Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	DS-9632NXI-I8/S
Facial Recognition	
Facial Detection and Analytics	Face picture comparison, human face capture, face picture search
Face Picture Library	Up to 16 face picture libraries, with up to 10,000 face pictures in total (each picture <= 15KB, total capacity <= 150 MB)

ComX Computers

Product Specification Sheet

Facial Detection and Analytics Performance	1-ch human face capture (HD network camera, up to 8 MP, H.264/H.265)
Face Picture Comparison	4-ch face picture comparison alarm
Perimeter Protection	
Human/Vehicle Analysis	Up to 4-ch 2 MP (H.264/H.265) video analysis for human and vehicle recognition
	Up to 12 rules in total
Recording	
Dual-stream	Support
Audio Compression	G.711ulaw / G.711alaw / G.722 / G.726 / MP2L2 / AAC
Video and Audio	
IP Video Input	32-ch
	Up to 12 MP resolution
	*: 32 MP and 24 MP is only available for channel 1 when ultra HD resolution mode is enabled.
HDMI 1 Output	4K
	(3840 x 2160)/60Hz, 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60Hz, 1920 x
	1080/60Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x
	768/60Hz
HDMI 2 Output	1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
VGA 1 Output	1-ch, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
Video Output Mode	HDMI1/VGA simultaneous output, HDMI2/VGA independent output
Incoming Bandwidth	320 Mbps
Outgoing Bandwidth	256 Mbps
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 Kohm)
Decoding	
Decoding Format	H.265+/H.265/H.264+/H.264/MPEG4
Decoding Capability	16-ch@1080p (30 fps)
Synchronous playback	32-ch
Stream Type	Video, Video & Audio
Network	
Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS
Remote Connection	128
Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	8 SATA interfaces
eSATA	1 eSATA interface
Capacity	Up to 10 TB capacity for each disk

ComX Computers

Product Specification Sheet

Serial Interface	RS-485 (full-duplex), RS-232, Keyboard
USB Interface	Front panel: 2 x USB 2.0, Rear panel: 1 x USB 3.0
Alarm In/Out	16/8
General	
Power Supply	100 to 240 VAC, 50 to 60 Hz
Consumption	<= 30 W
Working Temperature	-10 degreesC to 55 degreesC (14 degreesF to 131 degreesF)
Working Humidity	10% to 90%
Chassis	2U chassis
Dimension (W x D x H)	442 x 459 x 92 mm (17.4"x 18" x 3.6")
	<= 8.7 kg (19.2 lb.)
Certification	
FCC	Part 15 Subpart B, ANSI C63.4-2014
CE	EN 55032:2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4
Obtained Certification	CE, FCC, IC

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/DS-9632NXI-I8-S-Hikvision-AcuSense-32-channel-2U-4K-Buy-p-283867.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-24 02:37:31.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.