

E3SUPS10KHB

Schneider Easy UPS 3S 10kVA, 10kW 400V 3:3 UPS Low Tower for external batteries

Product Overview

Schneider Easy UPS 3S 10kVA, 10kW 400V 3:3 UPS Low Tower for external batteries



Specifications

Overview:

High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 10 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is supplied without batteries, so you can easily customize the battery solution.

Features:

Easy Loop Test

Verifies UPS performance before you connect your load, without the need for a load bank.

Intuitive user interface

The intuitive graphical user interface allows for easy system configuration.

Easy to install fast

Quickly roll the compact and lightweight UPS into position.

Front-access servicing

Simplifies installation and UPS maintenance while minimizing space requirements.

Straightforward installation

Including the input, output, and bypass breakers, as well as the Emergency Power Off (EPO) switch, simplifies installation planning and speeds up deployment.

ECO Mode

Operating mode that by-passes unused electrical components in good power conditions to achieve high operating efficiency without sacrificing protection

ComX Computers

Product Specification Sheet

Replaceable dust filters

protect the UPS in harsh environments.

Parallel capability

Multiple units can be placed in parallel to meet power capacity and redundancy requirements

Wide Input Voltage Window

Saves your battery power for when you really need it - during power cuts!

Optional SNMP Card

When you purchase the SNMP card, you can monitor and manage UPS status remotely through the UPS Web interface or through EcoStruxure IT's cloud-based and on-premise software suites.

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	E3SUPS10KHB
--------------	-------------

Output

Output power capacity	10.0 KWatts / 10.0 kVA
Max Configurable Power (Watts)	10.0 KWatts / 10.0 kVA
Nominal Output Voltage	400V 3PH
Output Voltage Distortion	Less than 3%
Output Frequency (sync to mains)	50 Hz, 60 Hz
Other Output Voltages	380, 415
Load Crest Factor	3 :: 1
Topology	Double Conversion Online
Overload Operation	150% for 1 minute 125% for 10 minutes
Output Voltage THD	< 3% linear load
Bypass	Built-in Maintenance Bypass

Input

Nominal Input Voltage	400V 3PH
Input frequency	45 - 65 Hz
Input voltage range for main operations	304 - 477V
Input Total Harmonic Distortion	Less than 3% for full load
Other Input Voltages	380, 415
Maximum Input Current	18.0A
Input Power Factor at Full Load	0.99

Batteries & Runtime

ComX Computers

Product Specification Sheet

Battery type	No internal battery - uses external battery system
Communications & Management	
Interface Port(s)	E3S_Parallel, E3S_TempSensor
Physical	
Maximum Height	530mm, 53.0CM
Maximum Width	250mm, 25.0CM
Maximum Depth	700mm, 70.0CM
Net Weight	36.0KG
Shipping weight	50.0KG
Shipping Height	772mm, 77.2CM
Shipping Width	400mm, 40.0CM
Shipping Depth	700mm, 70.0CM
Color	White
Environmental	
Operating Temperature	0 - 40 degreesC
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-984.3meters
Storage Temperature	-15 - 40 degreesC
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-14763.6meters
Audible noise at 1 meter from surface of unit	60.0dBA
Online thermal dissipation	516.0BTU/hr
Protection Class	IP 20
Conformance	
Approvals	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/E3SUPS10KHB-Schneider-Easy-UPS-3S-10kVA-10kW-400V-3-Buy-p-231663.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-09 23:45:10.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other

ComX Computers

Product Specification Sheet

information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.