

EAP115-WALL

TP-Link EAP115 Wall 300 Mbps Wireless N Wall-Plate Access Point

Product Overview

TP-Link EAP115 wall 300 Mbps Wireless N Wall-Plate Access Point, 2x 10/100 Mbps Ethernet (RJ-45) Ports, 2x internal 1.8dBi Omni antenna, Wall plate mounting, 100+ Wireless Client capacity, PoE (IEEE 802.3af) Power Supply



Specifications

Overview:

EAP115-Wall - 300Mbps Wireless N Wall-Plate Access Point

- Easy-mount construction allows installation into any standard EU-type data wall-box
- Compact, low-profile design fits discreetly with any existing interior style
- Free Auranet Controller Software enables administrators to easily manage hundreds of EAPs
- Support Power over Ethernet (802.3af) for convenient and affordable installation
- Enterprise class Wi-Fi security helps to decrease network security threats
- Captive portal provides one convenient method of authentication for Wi-Fi guests

Features:

- Easy-mount construction enables easy installation into any standard EU-type data wall-box
- Sleek, compact design blends perfectly with the existing interior style.
- Free Auranet Controller Software enables administrators to easily manage hundreds of EAPs
- Support Power over Ethernet(802.3af) for convenient and affordable installation
- 300Mbps wireless data rate for uninterrupted wireless connection
- Captive portal provides one convenient method of authentication for Wi-Fi guests
- Access Control restricts or allows the client to access the specified network segment
- Reboot Schedule enables all the APs to be rebooted automatically within a specified time
- WPA/WPA2-enterprise, 802.1X with RADIUS secure authentication and rogue access point detection ensure the security of WLAN
- Compatible with 802.11 b/g/n products
- QoS function prioritizes data, voice, and video applications to ensure time-sensitive traffic takes priority over all other traffic
- Multiple operating modes satisfy different application conditions including managed AP and standalone AP modes
- Load balance ensures large numbers of users have smooth network experiences in large business networks
- Multi-SSID divides multiple wireless network for different users
- Rate limit on per SSID to restrict the bandwidth of each client

Perfectly Formed

The EAP115-Wall would blend seamlessly into any business setting with a refined, minimalist appearance. A slimline design includes casing that's just 11 mm in thickness.

Effortless Deployment

With 802.3af Power over Ethernet supported there's no need for additional wiring. Simply plug in existing Ethernet cables and you're ready to go.

Complete Wireless Coverage

An EAP in each room guarantees a strong wireless signal and allows guests to enjoy their own private Wi-Fi network.

Centralized Management

Manage and monitor hundreds of EAPs with ease, all from a single location. TP-Link's free Auranet Controller Software provides an intuitive management interface with no special training required. Wi-Fi management has never been so simple or cost-effective.

Customized Guest Authentication with Captive Portal

Captive portal provides a convenient method of authentication for Wi-Fi guests. Choose from a range of authentication options and create a unique authentication page to advertise your business to users.

Specifications:

ComX Computers

Product Specification Sheet

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	EAP115-WALL
--------------	-------------

HARDWARE FEATURES

Interface	10/100Mbps Ethernet (RJ-45) Port *2
-----------	-------------------------------------

Physical Security Lock	-
------------------------	---

Button	LED/Wi-Fi Button, RESET
--------	-------------------------

Power Supply	PoE(IEEE 802.3af)
--------------	-------------------

Power Consumption	2.8 W
-------------------	-------

Dimensions (W x D x H)	3.4 x 3.4 x 1.2 in. (86.8*86.8*30.2 mm)
--------------------------	---

Antenna Type	Internal 2*1.8dBi Omni
--------------	------------------------

Mounting	Wall Plate Mounting
----------	---------------------

Watch Dog	Yes
-----------	-----

Hardware Watch Dog	Yes
--------------------	-----

WIRELESS FEATURES

Wireless Client Capacity	100+
--------------------------	------

Wireless Standards	IEEE 802.11n/g/b/a
--------------------	--------------------

Frequency	2.4GHz
-----------	--------

Signal Rate	11n: Up to 300Mbps(dynamic)
-------------	-----------------------------

11g: Up to 54Mbps(dynamic)

11b: Up to 11Mbps(dynamic)

Transmit Power	CE :
----------------	------

--

Wireless Functions	Multiple SSIDs(Up to 8 SSIDs)
--------------------	-------------------------------

Enable/Disable Wireless Radio

Automatic Channel Assignment

Transmit Power Control (Adjust Transmit Power on dBm)

QoS(WMM)

Load Balance

Rate Limit

Reboot Schedule

Wireless Schedule

Wireless Statistics based on SSID/AP/Client

ComX Computers

Product Specification Sheet

Wireless Security	Captive Portal Authentication
	Access Control
	Wireless Mac Address Filtering
	Wireless Isolation Between Clients
	SSID to VLAN Mapping
	Rogue AP Detection
	802.1X Support
	64/128/152-bit WEP / WPA / WPA2-Enterprise
	WPA-PSK / WPA2-PSK
MANAGEMENT	
Omada App	Yes
Centralized Management	Omada Hardware Controller (OC300)
	Omada Hardware Controller (OC200)
	Omada Software Controller
Cloud Access	Yes. Requiring the use of OC300, OC200, or Omada Software Controller.
EAP Controller Software	Yes
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c
System Logging Local/Remote Syslog	Local/Remote Syslog
Telnet	Yes
SSH	Yes
Web-based Management	HTTP/HTTPS
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
OTHERS	
Certification	CE, RoHS
Package Contents	300Mbps Wireless N Wall-Plate Access Point EAP115-Wall
	Installation Guide
	Mounting Screw
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10

ComX Computers

Product Specification Sheet

Environment	Operating Temperature: 0 degreesC~40 degreesC (32 degreesF~104 degreesF)
	Storage Temperature: -40 degreesC~70 degreesC (-40 degreesF~158 degreesF)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/EAP115-WALL-TP-Link-EAP115-Wall-300-Mbps-Wireless-N-Buy-p-304206.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-07 19:09:52.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.