EAP773

TP-Link EAP773 Omada BE9300 Ceiling Mount Tri-Band Wi-Fi 7 Access Point

Product Overview

TP-Link EAP773 Omada BE9300 Ceiling Mount Tri-Band Wi-Fi 7 Access Point, PORT: 1x10G RJ45 Port, SPEED:574Mbps at 2.4 GHz 2880 Mbps at 5 GHz 5760 Mbps at 6 GHz, FEATURE: 802.3bt POE and 12V DC (Power Adapter is not included), 4xInternal Antennas, MU-MIMO, 320MHz Support





Specifications

Features:

- BE9300 Tri-Band Wi-Fi 7: 5760 Mbps (6 GHz) 2880 Mbps (5 GHz) 574 Mbps (2.4 GHz). Buffering will no longer be a problem.
- 1x 10G Port: Unlock the full potential of Wi-Fi 7.
- Clear 6 GHz Band: Brings cleaner and wider band resources to your Wi-Fi.
- 320 MHz Bandwidth: Up to 320 MHz bandwidth enables many more simultaneous transmissions at the fastest possible speeds.
- Low Latency and Interference: Multi-Link Operation, and Multi-RUs ensure high performance of your network.
- Advanced Functions:Supports centralized management, mesh, and AI roaming.

BE9300 WiFi 7 Speed
Supports up to 9213 Mbps for a bufferless network of your offices or retail.

Next-Gen WiFi 7
Enjoy a smooth network with higher throughput and lower interference.

Multi-Link Operation (MLO)
Enables devices to simultaneously send and receive data across different frequency bands and channels.

10G PoE Port
Boosts overall throughput and offers flexible deployment with a 10 Gbps PoE port.

Auto Channel Selection and Power Adjustment
Boost WiFi performance and minimize interference for your network.

Intelligent Power Management

Offers more reliable network operation for your business.

Centralized Cloud Management
Manage the whole network locally or from the cloud.

Omada Mesh Technology
More flexible and convenient wireless deployment.

Ultra-Thin Design
?220 mm x 32.5 mm elegant design brings more flexibility.

Supersized Throughput for Better Experiences
With the brand-new 6 GHz band open to applications, WiFi 7 supports extending channel width to 320 MHz. Compared to WiFi 6/6E, the doubled channel bandwidth of 6 GHz offers many more simultaneous transmissions at the fastest possible speeds. Making full use of these new resources, the throughout of EAP773 reaches up to 9213 Mbps.

Higher Capacity for Increased Traffic Demands
WiFi 7 supports 4096-QAM with 12 bits rather than WiFi 6's 10 bits. The updated modulation method enables each signal to carry more dense amounts of data. Equipped with advanced 4096-QAM, EAP773 empowers your business to meet ever-growing traffic demands from high-bandwidth applications, such as remote offices, HD video conferencing, and cloud-based applications.

Lower Latency for Boosted Network Reliability
EAP773 allows network devices to communicate across multiple bands and channels simultaneously thanks to Multi-Link Operation (MLO). Additionally, Multi Resource Units (Multi-RUs) open up previously wasted channels. More bands can be used concurrently to share redundant data, and the interference will be blocked to improve reliability.

Optimized Wired Performance with 10G PoE Port
With a 10 Gigabit Ethernet Port, EAP773 delivers remarkable multi-gigabit performance for higher bandwidth and faster WiFi. Compatibility with 802.3bt PoE is ideal for flexible deployment in large-scale scenes such as offices, schools, and hotels.

Auto Channel Selection and Power Adjustment
Provide powerful wireless performance while greatly reducing Wi-Fi interference by automatically adjusting the channel settings and transmission power levels of neighboring APs in the same network.*

Seamless Integration into Omada SDN
The Omada Software Defined Networking (SDN) platform integrates network devices including access points, switches, and routers to provide 100% centralized cloud management and create a highly scalable network-all controlled from a single interface. Experience total control at your fingertips.

Secure Guest Network with up to 24 SSIDs
Guest network access provides enhanced security to guests. Different SSIDs also enable flexible access management.

WPA3 for Worry-Free Open Public Networks
With advanced enterprise security, WPA3 provides more data security for previously unsecured and open WiFi hotspots.

Boost Your Business with SMS Login
Captive portal (including SMS and Voucher) and 802.1x authentication help maintain authorized guests to use the network. Boost your business with a customized marketing page.

Rogue AP Detection
Detect and mitigate rogue access points to protect your business network from security holes or other threats anywhere,

anytime.

Ultra-Thin Design for Flexible Deployment
The overall design of EAP773 utilizes a thinner circular arc with a groove around the top cover, fitting closer to various installation surfaces such as ceilings. The compact internal hardware layout and heat-dissipating design ensure high performance with a sharp aesthetic.

Specifications:

HARDWARE FEATURES	
Interface	1x 10G Ethernet Port
Button	Reset
Power Supply	802.3bt PoE or 12V/2.5A DC
Power Consumption	Support Smart Power Comsuption Management
	24.05 W (802.3bt, full functionality);
	20.92 W (12/2.5A, full functionality);
	22.4 W (802.3at decrease 6GHz Power);
	10.1. W (802.3af, radio off, only main chip and LAN working)
Dimensions (W x D x H)	8.7 x 8.7 x 1.3 in (220 x 220 x 32.5 mm)
Antenna Type	2.4 GHz: 2x 3.0 dBi
	5 GHz: 2x 3.0 dBi
	6 GHz: 2x 3.0 dBi
Bluetooth	1 x 4.0 dBi, Bluetooth 5.2
	*Firmware update may be required.
Mounting	Ceiling / Wall Mounting (Kits Included)
WIRELESS FEATURES	
Wireless Client Capacity	2 GHz: 128
	5 GHz: 128
	6 GHz: 128
Wireless Standards	IEEE 802.11 a/b/g/n/ac/ax/be
Frequency	6 GHz, 5 GHz, and 2.4 GHz
Signal Rate	574 Mbps (2.4 GHz) 2880 Mbps (5 GHz) 5760 Mbps (6 GHz)

Wireless Functions	MLO
	4K-QAM
	MU-MIMO
	HE320
	Mesh
	BBS Coloring
	OFDMA
	Load Balance
	Band Steering
	Beamforming
	Airtime Fairness
	Multiple SSIDS:24(8 on each band)
	Wireless Schedule
	Reboot Schedule
	QoS(WMM)
	Rate Limit
	Static IP/Dynamic IP
	RADIUS Accounting
	MAC Authentication
Wireless Security	Captive Portal Authentication
	Access Control
	Maximum number of MAC Filter: 4,000
	Wireless Isolation Between Clients
	VLAN
	Rogue AP Detection
	WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise
Transmission Power	< 20 dBm (2.4 GHz, EIRP)
	< 23 dBm (5 GHz, band 1&band 2, EIRP)
	< 28 dBm (5 GHz, band 3, EIRP)
	< 23dBm (6 GHz, EIRP)
MANAGEMENT	
Omada App	Yes
Centralized Management	Omada Cloud-Based Controller
	Omada Hardware Controller (OC300)
	Omada Hardware Controller (OC200)
	Omada Software Controller

Cloud Access	Yes. Require the use of an OC300, OC200, Omada Software Controller, or an Omada Cloud-Based Controller.
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c, v3
System Logging Local/Remote Syslog	Yes
Web-based Management	Yes
OTHERS	
Certification	CE, FCC, RoHS, IC
Package Contents	EAP773
	Installation Guide
	Ceiling/Wall Mounting Kits
	Note: Power Adapter is NOT included.
Environment	Operating Temperature: 0 degreesC-40 degreesC (32 degreesF-104 degreesF);
	Storage Temperature: -40 degreesC-70 degreesC (-40 degreesF-158 degreesF);
	Operating Humidity: 10%-90% non-condensing;
	Storage Humidity: 5%-90% non-condensing;

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx.co.za/EAP773-TP-Link-EAP773-Omada-BE9300-Ceiling-Mount-Tri-Band-Wi-Fi-7-Access-Point-p-303257.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx.co.za/terms-of-use.php
Terms of Sale: https://www.comx.co.za/terms-of-sale.php

PDF generated: 2026-11-01 20:31:01.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.