

FAN-X3S

Fanvil X3S 2SIP Colour screen VoIP phone with PSU - no PoE

Product Overview

Fanvil X3S 2SIP Colour screen VoIP phone with PSU - no PoE, HD voice, Two Network interfaces (10M/100M), 128 x 50 graphic LCD Display, RJ9 headset Port, External Power Supply, Caller ID Display (Power supply included - No POE)



Specifications

Overview:

Fanvil's FAN-X3S IP Phone offers simplicity, elegance and a superior user experience. The FAN-X3S features 2 SIP lines, HD Voice, and colour LCD screen, a smart user interface for easy installation and configuration.

The FAN-X3S is compatible with major platforms and comes with a Power Supply included.

Note: The FAN-X3S does NOT support PoE

POE:No

Power supply included:Yes - 5V

Features:

- HD Voice
- X3P: Power over ethernet
- Two Network interfaces (10M/100M)
- 2-SIP Line Executive IP Phone
- SIP2.0(RFC3261) & Correlative RFCs
- Support L2TP and Open VPN
- 128*50 Graphic LCD Display
- RJ9 Headset Port
- Smart and friendly user interface

Main Features

- 2 SIP Lines
- HD Voice
- User Friendly Graphical Menu with Help description
- POE Enabled
- Handset (HS) / Hands-free (HF) / Headphone (HP) mode
- Desktop / Wall-mount installation
- External Power Supply (X3)
- Economical and Environmental friendly package
- Industrial Standard Certifications: CE/FCC

Call Features

- Call out / answer / reject
- Mute / Unmute (microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (depending on server)
- Redial
- Do-Not-Disturb (per line / per phone)

ComX Computers

Product Specification Sheet

- Auto-Answering (per line)
- Voice Message (on server)
- Local 3-way Conference
- Hot Line

Phone Features

- Initialization Configuration Wizard
- Up to 5 User Accounts / Profiles with individual phonebook/call log/configurations/PIN
- Phone Accessibility Control by User PIN
- Intelligent Phonebook (up to 500 entries total)
- Cloud Phonebook (XML)
- Intelligent Contact Number Matching / Filtering
- Call log (300 entries total, in/out/missed)
- Call Connection Quality (QoS) Measurement and Indication
- Voice Message Waiting Indication (VMWI)
- Network Time Synchronization

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	FAN-X3S
Generic	2 SIP Lines
	HD Voice
	POE Enabled(X3SP/X3G)
	Handset(HS) / Hands-free(HF) / Headphone(HP) mode (EHS support for Plantronics headsets)
	Desktop / Wall-mount installation
	Economical and Environmental friendly package
	Industrial Standard Certifications: CE/FCC

ComX Computers

Product Specification Sheet

Call Features	Call out / answer / reject
	Mute / unmute (microphone)
	Call Hold / Resume
	Call Waiting
	Intercom
	Caller ID Display
	Call Forwarding (Always/Busy/No Answer)
	Call Transfer (Attended/Unattended)
	Call Parking/Pick-up (depending on server)
	Redial
	Do-Not-Disturb (per line / per phone)
	Auto-Answering (per line)
	Voice Message (on server)
	Local 3-way Conference
	Hot Line
Phone Features	Phone Accessibility Control by User PIN
	Intelligent Phonebook (up to 500 entries total)
	Remote Phonebook (XML/LDAP)
	Intelligent Contact Number Matching / Filtering
	Call log (300 entries total, in/out/missed)
	Voice Message Waiting Indication (VMWI)
	Network Time Synchronization
	Multi-language support in screen and web UI: English, Chinese(Traditional/Simplified), Japanese, Russian, Italian, Turkish, Germany, Dutch, Spanish, Hebrew, Polish, French etc.
Audio	HD Voice Microphone/Speaker (Handset/Hands-free, 0~7KHz Frequency Response)
	Wideband ADC/DAC 16KHz Sampling
	Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB
	Wideband CODEC: G.722
	Full-duplex Acoustic Echo Canceller (AEC) - Hands-free Mode, 96ms tail-length
	Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
	Packet Loss Concealment (PLC)
	Dynamic Adaptive Jitter Buffer up to 300ms
	DTMF: In-band, Out-of-Band - DTMF-Relay (RFC2833) / SIP INFO
Networking	Physical: 10/100Mbps(X3S/X3SP), 10/100/1000Mbps(X3G) Ethernet, dual bridged port for PC bypass
	IP Configuration: Static / DHCP / PPPoE

ComX Computers

Product Specification Sheet

Network Access Control: 802.1x	VPN: L2TP (Basic Unencrypted) / OpenVPN
	VLAN
	QoS
Protocols	SIP2.0 over UDP/TCP/TLS
	RTP/RTCP/SRTP
	STUN
	DHCP
	PPPoE
	802.1x
	L2TP (Basic Unencrypted)
	OpenVPN
	SNTP
	FTP/TFTP
	HTTP/HTTPS
	TR069
RFCs	354/1321/1350/1769/1889/ 1890/2131/2132/
	2616/2617/2661/2833/2976/ 3261/3262/3263/
	3264/3265/3268/3311/ 3489/ 3711/4346/4566/
	5630/5865
Deployment & Maintenance	Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/ DHCP/OPT66/SIP PNP/ TR069
	Web Management Portal
	Web-based Packet Dump
	Configuration Backup/Restore
	Auto/Manual Online Software Upgrade
	Syslog

ComX Computers

Product Specification Sheet

Physical Specifications	LCD x1: 2.4/2.8 inch (320x240) color-screen LCD
	Keypad: 32 keys, including
	4 Soft-keys
	12 Standard Phone Digits keys
	5 Navigation keys
	2 Line keys with tri-color LED
	5 Function key
	3 Volume Control keys, Up/Down/Mute(Microphone)
	1 Hands-free
	HD Hands-free Speaker (0 ~ 7KHz) x1
	HD Hands-free Microphone (0 ~ 7KHz) x1
	HD Handset (RJ9) x1
	Standard RJ9 Handset Wire x1
	1.5M CAT5 Ethernet Cable x1
	RJ9 Phone Jacket x2: Handset x1, Headphone x1
	RJ45 Ethernet Jacket x2: Network x1 (802.3AF POE Class 1 Enabled), PC x1 (Bridged to Network)
	Main Chipset: Broadcom
	DC Power Input: 5V/600mA
	Working Temperature: 0 ~ 40degreesC
	Working Humidity: 10 ~ 65%
	Dual-Functional Back Rack x1: Desktop Stand / Wall-mount
	Color: Black
	Package Dimensions: 275x215x62mm (W x H x L)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/FAN-X3S-Fanvil-X3S-2SIP-Colour-screen-VoIP-phone-with-Buy-p-311058.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-08 17:16:27.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

ComX Computers

Product Specification Sheet

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.