

FS1026PS1

Cudy FS1026PS1 24-Port RJ-45 10/100M+2 Gigabit RJ-45 +1 Gigabit Combo ports with 24 POE Ports Switch

Product Overview

Cudy FS1026PS1 24-Port RJ-45 10/100M+2 Gigabit RJ-45 +1 Gigabit Combo ports with 24 POE Ports Switch with Built-in power supply, support 16-port IEEE 802.3at PoE+ Injector, Steel case 300W Internal



Specifications

Overview:

The Cudy FS1026PS1 26-Port 10/100M PoE+ Switch with 1 FSP Slot allows you to manage your home or office network with ease. It features 24 Ethernet PoE ports with 2 uplink ports and 1 SFP slot. Its PoE RJ-45 connectors support any 10/100Mbps Ethernet devices, while the 2 non-PoE uplink ports support 10/100/1000Mbps Ethernet devices and it's compliant with IEEE 802.3af/802.3at network standards.

Used for many applications the Cudy FS1026PS1 works with IP Cameras for home, office or small businesses. It also works well with PCs, printers and access points in your home or office, making it ideal for small businesses. It even features a VLAN mode for additional security, this allows the ports to be isolated from one another.

Its simple plug and play interface makes it incredibly easy to use. Its sturdy design is made from high-quality metal. This gives you a longer service life and provides better heat dissipation, making it suitable for most environments. It also features a fanless design with venting holes to help dissipate heat with silent operation.

Watchdog guarantees the uninterrupted operation of your PoE devices. The PoE watchdog continuously monitors the connection status of remote hosts. If an error is detected on the remote PoE device, the PoE switch immediately restarts the device to bring it back to normal operation.

Features:

- 24 x 10/100M PoE+ ports
- 2 x Gigabit Uplink port
- 1 x 1.25Gbps SFP slot
- 300 Watts PoE power budget
- IEEE 802.3at / IEEE 802.3af standard compliant

ComX Computers

Product Specification Sheet

- Plug&play, simple setup with no configuration needed

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	FS1026PS1
Connector Type	24-Port 10/100M PoE+ Switch with 2 Gigabit Uplink Ports and 1 SFP Slot
Network Protocols	IEEE802.3
	IEEE802.3u
	IEEE802.3ab
	IEEE802.3x
	IEEE802.3z
PoE Parameters	PoE Standard: IEEE802.3af /IEEE802.3at
	Max each port: 15.4W (IEEE 802.3af)
	Max each port : 30W (IEEE 802.3at)
	PoE compatibility: IEEE 802.3af/at adaptive
	PoE port output: DC48-55V
	Power Pin : Power over spare pairs 1/2(+), 3/6 (-)
Network Media	10BASE-T: Cat 6 UTP(<=250 meters)
	100BASE-TX: Cat5 or more UTP (<=100 meters)
	1000BASE-TX: Cat5 or more UTP (<=100 meters)
Optical	Multi-Mode Fiber: 850nm, 1310nm
	Transmission Distance: 550m/2Km
	Single-Mode Fiber: 1310nm, 1550nm
	Transmission Distance: 20/40/60/80/100/120km
Performance Specification	Bandwidth: 10.8Gbps
	MAC Address: 2K
	Packet Buffer Memory: 1M
	Packet Forwarding Rate: 8Mpps
	Forwarding Mode: Store-And-Forward
Power Supply	Product Input Voltage: AC100-240V 50/60Hz
	Output: 52V5.76A, Power Budget: 300W

ComX Computers

Product Specification Sheet

Led indicator	PWR - Power supply indicator(Red):
	Lighting: Powered
	Un-Light: No Power
	SW - DIP indicator(Green):
	OFF: Normal
	Vlan: Lighting
	Extend: Slow flash
	1-27 - RJ-45 ACT indicator(Green):
	Lighting: Connecting
	Flashing: Data Transmit
	Un-Light: Disconnect
MTBF	100,000 hours
Product Dimensions	32 x 21 x 4.6 cm
Product Weight	1900g

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/FS1026PS1-Cudy-FS1026PS1-24-Port-RJ-45-10-100M-2-Gigabit-Buy-p-261551.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-11 06:23:41.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.