

GS-GDS3726

Grandstream GDS3726 SIP DoorPhone Intercom with 4MP Video camera with doorbell key

Product Overview

Grandstream GDS3726 SIP DoorPhone Intercom with 4MP Video camera, IK10, RFID, 1 doorbell key, IP Access Control system, Metal casing, IK10 Vandal-resistant, IP66, NFC, Bluetooth, 6x White Light LED for day & night, Up to 1920x1080 Max Video Resolution, 30 frames per second Max Frame rate, Up to 2560x1440 snapshots, 3-5m adjustable sensitivity PIR, Ai-based Motion Detection, Two Microphone, 3W Speaker, Up to 5000 RFID supported, 2x Relay (Ssr) Access Control, 3x Alarm in, 2x Alarm out, 1x RJ45 one 10/100 Mbps Port with Integrated PoE, RS485, Wiegand 26 / 34 Input and Output, SD card slot



Specifications

Overview Summary:

The Grandstream GDS3726 SIP DoorPhone Intercom offers an advanced security solution perfect for both residential and commercial properties. This high-performance device combines video surveillance, access control, and communication into a single unit. Featuring a 4MP camera with HD video resolution and AI-powered motion detection, the GDS3726 ensures that you can monitor your property effectively both day and night. It supports multiple access methods, including RFID, Bluetooth, NFC, PIN, and SIP calls, offering flexibility for different security needs. Whether you're at home or on the go, the device integrates seamlessly with Grandstream's GDS Manager software and mobile app for easy control and monitoring. Buy now and upgrade your property's security with this top-tier, weather-resistant intercom system.

Performance tier:Premium

Uses:Residential security, commercial building security, access control, video surveillance, intercom systems

Overview:

Grandstream GDS3726 SIP DoorPhone Intercom: Advanced Security Solution for Modern Buildings

The Grandstream GDS3726 SIP DoorPhone Intercom combines cutting-edge video surveillance with advanced access control features, creating a powerful security solution for residential and commercial properties. Designed to streamline building entry and enhance security, this device offers a wide range of functionalities that integrate seamlessly into modern smart security systems.

Description:

The GDS3726 is an IP video door system that features a 4MP camera, providing crystal-clear video resolution up to 1920x1080 . Its durable, metal casing ensures protection against weather and vandalism, boasting an IP66 weatherproof rating and IK10 vandal resistance. The device integrates easily with Grandstream's GDS Manager software and mobile app for convenient control, making it suitable for various security needs. With advanced features such as AI-based motion detection, dual microphones, and a speaker with noise reduction, this device ensures high-quality communication and reliable security monitoring.

Features:

Key Features of the Grandstream GDS3726

High-Resolution Video Surveillance

The Grandstream GDS3726 comes equipped with a 4MP camera capable of delivering video in 1080p Full HD, with up to 2560x1440 snapshot resolution. Featuring a 152degrees wide-angle lens, it offers a clear, comprehensive view of your entrance area, both day and night. With enhanced low-light performance and six white light LEDs, this system ensures visibility in a variety of lighting conditions.

Reliable Access Control with Multiple Entry Methods

This smart door system supports a variety of access methods, allowing users to enter via PIN, IC/ID cards, NFC, Bluetooth (BLE), a mobile app, QR codes, or even through SIP calls. This flexibility ensures that the GDS3726 can meet the needs of any environment, whether it's a residential home or a commercial facility.

AI-Powered Motion Detection and Intrusion Alerts

The GDS3726 integrates AI-based motion detection technology to improve security by identifying unusual activity around your entrance. The system's built-in PIR (Passive Infrared) sensor provides up to 5 meters of adjustable sensitivity, reducing false alerts and improving response accuracy. It also features intelligent LED lighting that activates based on motion, enhancing visibility and safety.

Enhanced Communication with Dual Microphones and Speakers

Featuring dual microphones and a 3W speaker, the GDS3726 ensures clear two-way communication. The system also includes AI-powered noise reduction, which improves audio quality by filtering out background noise during conversations, making it easier to hear and respond clearly.

Robust and Durable Design

Housed in a sturdy metal casing, the GDS3726 is built to withstand the elements. Its IP66 weatherproof rating makes it resistant to rain, dust, and other harsh conditions, while its IK10 vandal-resistant rating ensures it can handle potential impacts and tampering.

Seamless Integration and Centralized Control

This device integrates with Grandstream's GDS Manager software and mobile app, allowing users to manage and monitor security systems from a central location. With cloud support and mobile app integration, the GDS3726 enables remote access, giving property managers and homeowners the flexibility to control access and monitor activity anytime, anywhere.

Security and Monitoring Capabilities

The GDS3726 supports multiple alarm inputs and outputs, along with an SD card slot for storing video recordings. It also features two relay access control outputs, enhancing the device's versatility in different security setups. The built-in solid-state relay (SSR) ensures strong protection against external magnetic interference, making it a highly secure solution for your property.

Specifications Overview:

ComX Computers

Product Specification Sheet

- Camera: 4MP, 1920x1080 max resolution, 152degrees wide-angle lens, HDR, WDR, AI Intelligent Fill Light
- Weatherproof: IP66 rating for protection against the elements
- Vandal Resistance: IK10 rated for impact resistance
- Access Control: PIN, IC/ID cards, NFC, BLE, SIP Call, QR-Code, mobile app
- Audio: Dual microphones, 3W speaker, AI noise reduction
- Power: PoE (Power over Ethernet)
- Connectivity: 1x RJ45 (10/100 Mbps), RS485, Wiegand 26/34 Input/Output
- Storage: SD card slot for video storage
- Security: Solid-state relay for magnetic interference protection, AI-powered motion detection, 3-5 meter PIR sensor
- Alarm Inputs/Outputs: 3x alarm inputs, 2x alarm outputs

Why Choose the Grandstream GDS3726

Whether you're securing a home, office, or commercial building, the Grandstream GDS3726 SIP DoorPhone Intercom offers a comprehensive security solution that combines video surveillance, access control, and communication in one compact device. With its high-definition camera, advanced motion detection, and reliable access control options, it provides peace of mind knowing your property is protected. The ease of integration, along with cloud and mobile app support, makes it ideal for both residential and business environments.

For those seeking a robust, feature-rich security solution, the Grandstream GDS3726 is the ideal choice.

Specifications:

© 2025 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	GS-GDS3726
MODEL	GDS3726
VIDEO COMPRESSION	H.265 Main Profile, H.264 High Profile / Main Profile / Base Profile, Motion JPEG
IMAGE SENSOR RESOLUTION	1/3", 4MP, HDR
LENS TYPE	F2.2, FOV: 127degrees(H) x 70degrees(V) x 152degrees(D)
DAY & NIGHT	White light, 6x LED
MAX VIDEO RESOLUTION	Video: upto 1920*1080, Snapshots: upto 2560*1440
MAX FRAME RATE	30 frames per second
WIDE DYNAMIC RANGE	Yes, up to 120db
PIR	Supported, 3-5m, adjustable sensitivity
AI ISP	Supported
EMBEDDED ANALYTICS	AI-based Motion detection
MICROPHONE	Two mics
SPEAKER	3W
APPLICATION AND GDS MANAGER	Support Cloud, Access Control Mobile App, and GDS Manager Application
SNAPSHOTS	Triggered upon events, sent to Email, FTP Server, GDS Manager, Cloud Server, Access Control App and/or Local.

ComX Computers

Product Specification Sheet

NETWORK PROTOCOL	TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS local upload and mass provisioning using TR-069, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, SSH, SMTP, TFTP, NTP, STUN, SIMPLE, TLS, SRTP
BLUETOOTH	BLE 5.0
TELEPHONY FEATURES	SIP Paging, Multicast Paging, call-waiting with priority override, Account Sharing
VOICE CODECS	G.711μ/a, G.722 (wide-band), G.726-32, G.729 in-band and out-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC, ANS
VIDEO CODECS	H264, H265
QOS	Layer 2 (802.1Q, 802.1p), 802.11e and Layer 3 (ToS, DiffServ, MPLS) QoS
SECURITY	User and administrator level passwords, Ed25519 and X25519 based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control
UPGRADE/PROVISIONING	Firmware upgrade via TFTP/HTTP/HTTPS, mass provisioning using TR-069 or AES encrypted XML configuration file
BUTTON	1 doorbell key
	1 anti-tamper button
	1 reset button
RFID	13.56MHz&125kHz , MIFARE Classic 1K, MIFARE Classic 4K, MIFARE Ultralight, MIFARE Ultralight C, MIFARE PLUS and MIFARE DESFire
ACCESS CONTROL	2x Relay (SSR)
ALARM INPUT	3x Alarm in
ALARM OUTPUT	2x Alarm out
NETWORK INTERFACE	1x RJ45, One 10/100 Mbps port with integrated PoE
EXPANSION INTERFACE	RS485, Wiegand 26/34 input and output, SD card slot
SD CARD	Maximum capacity 256GB
POWER & GREEN ENERGY EFFICIENCY	DC power supply: DC 12V/1A, 9~36V
	POE: 802.3af class3
INGRESS PROTECTION	Weatherproof, vandal resistant, with support for extra back reinforcing metal plate
DIMENSIONS (H X W X D)	Unit: 203mm*86mm*33.5mm
INTEROPERABILITY	ONVIF (Profile S)
PACKAGE	GDS3726 Device
	Quick Installation Guide, Rain Cover (Optional)
	Wall Bracket
	13.56Mhz RFID Cards
TEMPERATURE AND HUMIDITY	Operating Temperature: - 30 - +60degreesC
	Operating Humidity: 10-90% (non-condensing)
	Storage Temperature: -30 - +70degreesC
	Storage Humidity: 10-90% (non-condensing)
PROTECTION CLASS	IP66 (EN60529)
	IK10 (IEC62262) for both metal surface/buttons and lens area

ComX Computers

Product Specification Sheet

COMPLIANCE	FCC, CE, RCM, IC
------------	------------------

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/GS-GDS3726-Grandstream-GDS3726-SIP-DoorPhone-Intercom-Buy-p-331297.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-07 20:26:17.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.