

MT-RBCAP-AC

MikroTik cAP AC - Dual band AC Indoor Access Point with PoE passthrough, 2x Gigabit LAN

Product Overview

MikroTik cAP AC - Dual band AC Indoor Access Point with PoE passthrough, RouterOS 4, 4 Core 716 MHz IPQ-4018 CPU, 128 MB Ram, 16 MB Storage size, 802.3af/at PoE in, 17-57 V PoE in input Voltage, 2x Gigabit Ethernet ports, 802.11b/g/n Wireless 2.4 GHz standard with 2 chains, 802.11ac Wireless 5 GHz standards with 2 chains



Specifications

Overview:

The cAP ac is a very capable and powerful wireless access point that looks beautiful on both walls and ceilings. The concurrent dual band wireless radio supports dual chain 2 GHz 802.11b/g/n and 5 GHz in a/n/ac standards, and will provide coverage in 360 degrees around it.

Even though the radio supports repeater mode, the two Ethernet ports give you the ability to extend your network with cables, even if PoE power is required, since the cAP ac supports 802.3af/at PoE input on the first port, and passive PoE output on the second port.

Specifications:

© 2018 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	MT-RBCAP-AC
Product code	RBcAPGi-5acD2nD
Architecture	ARM 32bit
CPU	IPQ-4018
CPU core count	4
CPU nominal frequency	716 MHz
Dimensions	Round case: Ø 136 mm, height: 30 mm, Square case: 145 mm x 145 mm x 30 mm
License level	4

ComX Computers

Product Specification Sheet

Operating System	RouterOS
Size of RAM	128 MB
Storage size	16 MB
Storage type	FLASH
Tested ambient temperature	-40 to 50 degrees C
Powering	
Max Power consumption	13W
PoE in	802.3af/at
PoE out	Passive PoE up to 57V
PoE in input Voltage	17-57 V
Number of DC inputs	1 (PoE-IN)
Wireless	
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	2
Wireless 2.4 GHz chip model	IPQ-4018
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11ac
Antenna gain dBi for 5 GHz	2.5
Wireless 5 GHz chip model	IPQ-4018
Ethernet	
10/100/1000 Ethernet ports	2

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/MT-RBCAP-AC-MikroTik-cAP-AC-Dual-band-AC-Indoor-Access-Buy-p-182107.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-09 16:06:38.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.