

POE-24V15W

Procet Gigabit 24V 15W PoE Adapter with no cable

Product Overview

Procet Gigabit 24V 15W PoE Adapter with no cable, EN15G-24-3, 1x LAN Port, 1x PoE Output Port, 1x AC inout, 10/100/1000 Mbps pass through Data rates



Specifications

Overview:

Procet's POE-24V15W is a Gigabit, 24V, 15W, 0.64A, surge-protected, midspan, passive PoE injector enclosed in an IP40 fire-retardant plastic case.

*Note:

Clover Power Cable Not Included.

Features:

EN15G-24-3 is a single port midspan Injector with 2 Pair output to 15 watts of power at 24Vdc, 0.64Amp.

Designed for the passive powered 15W PoE Powered Devices (PDs), such as IP Cameras, wi-reless APs, Microwave radio, IoT application, door locks, displays, POS, and information kiosks, It supports 10/100/1000Mbps of data rates.

Enclosed in an IP40 fire retardant plastic case, designed for indoor installation with a Wall-plug mouted. It operates with a wide input voltage of 100-240Vac, 50 or 60 Hz. The effective distance limitation of 100 meters over Cat5e/Cat6 cables

Specifications:

ComX Computers

Product Specification Sheet

© 2022 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	POE-24V15W
Key Features	Single-port
	10/100/1000Mbps
	Input 100-240Vac 0.5A 50/60Hz
	output 24Vdc 0.64A 15W
	Power pin: 4/5+, 7/8-
	Power cable with US/EU optional
	AC input: 3 wire
Part Number	EN15G-24-3
Ports condition	LAN Port*1, PoE Output Port*1, AC inout *1
Regulatory Compliance	passive
	RoHS Compliance
	WEEE Compliance
Pass Through Data Rates	10/100/1000 Mbps
Output	Pin Assignment and Polarity:
	4/5(+), 7/8(-)
	Output Power Voltage: 24Vdc
	User Port Power: 15W Guarantee
Input	Input Voltage: 100-240Vac
	Frequency: 50/60Hz Typ
Working Environment	Operating Temperature: 0 degreesC to 40 degreesC
	Operating Humidity: 20% to 80%, non-condensation
	Storage Temperature: -20 degreesC to 70 degreesC
	Storage Humidity: 10% to 90%, non-condensation
	Operating Altitude: up to 2000meters
AC Surge Protection	Line-Earth 1.2/50us (8/20us): 2KV
	Line-Line 1.2/50us (8/20us): 1KV

ComX Computers

Product Specification Sheet

Mechanical Characteristics	Case: Plastic
	Color: White
	Mounting: Wall-plug
	IP Rated: IP40
	Connectors: Shielded RJ-45*2
	Size: 85*46*30mm
	Weight: 100g(0.27lb)
LED Indicator	Power Indicator: Yellow
	PoE Load Indicator: Green
Safety Approvals	CE, FCC

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/POE-24V15W-Procet-Gigabit-24V-15W-PoE-Adapter-with-Buy-p-262810.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-13 18:39:41.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.