

RBD52G-5HACD2HND-TC

MikroTik hAP AC2 Dual Band WiFi Router with 5x Gigabit ethernet ports

Product Overview

MikroTik hAP AC2 Dual Band WiFi Router 5x Gigabit Ethernet ports, Quad core cpu 716 MHz, RouterOS L4, Passive PoE, 802.11b/g/n Dual Chain 2.4 GHz Wireless, 802.11a/n/ac Dual Chain 5 GHz Wireless, 5x 10/100/1000 Ethernet port, 1x USB port, RBD52G-5HACD2HND-TC



Specifications

Overview:

hAP ac²

Dual-Concurrent 2.4/5GHz AP, 802.11a/b/g/n/ac, Five Gigabit Ethernet ports, USB for 3G/4G support, universal tower case and IPsec hardware encryption support

Features:

The hAP ac² is a Dual-concurrent Access Point, that provides Wifi coverage for 2.4 GHz and 5 GHz frequencies at the same time. Five 10/100/1000 Ethernet ports provide Gigabit connections for your wired devices, USB can be used for external storage or 4G/LTE modem, and device supports IPsec hardware acceleration.

New design universal case allows unit to be positioned either horizontally (desktop) or vertically (tower case). Wall anchored

ComX Computers

Product Specification Sheet

mounting kit is provided.

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	M-RBD52G-5HACD2HND-TC
--------------	-----------------------

Specifications

Product code	RBD52G-5HacD2HnD-TC
Architecture	ARM 32bit
CPU	IPQ-4018
CPU core count	4
CPU nominal frequency	716 MHz
Dimensions	34 x 119 x 98mm
License level	4
Operating System	RouterOS
Size of RAM	128 MB
Storage size	16 MB
Storage type	FLASH
Tested ambient temperature	-40degC .. +50degC

Powering

Max Power consumption	15W
PoE in	Passive PoE
PoE in input Voltage	18-28 V
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	12-30 V

Wireless

Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	2.5
Wireless 2.4 GHz chip model	IPQ-4018
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n/ac
Antenna gain dBi for 5 GHz	2.5
Wireless 5 GHz chip model	IPQ-4018

Ethernet

10/100/1000 Ethernet ports	5
----------------------------	---

ComX Computers

Product Specification Sheet

Peripherals	
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB type A
Max USB current (A)	1

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/M-RBD52G-5HACD2HND-TC-MikroTik-hAP-AC2-Dual-Band-WiFi-Buy-p-228001.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-16 08:06:06.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.