ComX Computers
Product Specification Sheet

RR-TX3E-28PK-R1

Coolermaster Hyper TX3 Evo CPU Air Cooler

Product Overview

CoolerMaster Hyper TX3 EVO, 3 Direct Contact Heat Pipes with a base engineered to Minimize CPU gaps, Excellent airflow design with compact heatsink dimensions, Compatibility: AMD Socket FM1, AM2, AM3, AM3+, Intel Socket LGA 1155, 1156, 1366, 2011, 1150







Specifications

Overview:

The Hyper TX3 EVO cooling system is designed and optimized to provide the best user experience and cooling potential for a new generation of processors.Optimized for current and future generation sockets, the Hyper TX3 EVO sees improvement in its Direct Contact heat pipe performance, expanded socket support, and a higher quality 92mm wide-range PWM fan.

Features:

- 3 direct contact heat pipes with a base that is engineered to minimize CPU contact gaps - providing excellent heat conduction.
- Option for adding 2nd fan with quick-snap fan brackets to increase cooling performance.
- A mere 17 dBA (minimum speed) is accomplished by utilizing a silent 92mm PWM fan with a wide RPM range.
- Versatile all-in-one mounting solution supporting the latest Intel LGA 1366 / 1155 and AMD FM1 / AM3+.

- Excellent airflow design with compact heat sink dimension.

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	RR-TX3E-28PK-R1
CPU Socket	Intel Socket:
	LGA 1366 / 1156 / 1155 / 775
	AMD Socket:
	FM1 / AM3+ / AM3 / AM2+ / AM2
CPU Support	Intel:
	Core i7 Extreme / Core i7 / Core i5 / Core i3 / Core2 Extreme / Core2 Quad / Core2 Duo / Pentium / Celeron
	AMD:
	FX-Series / A-Series / Phenom II X4 / Phenom II X3 / Phenom II X2 / Phenom X4 / Phenom X3 / Athlon II X4 / Athlon II X3 / Athlon II X2 / Athlon X2 / Athlon / Sempron
Dimension	90 x 79 x 136 mm (3.5 x 3.1 x 5.4 in)
Heat Sink Dimensions	90 x 51 x 136 mm (3.5 x 2.0 x 5.4 in)
Heat Sink Material	3 Direct Contact Heat Pipes / Aluminum Fins
Heat Sink Weight	306g (0.68 lb)
Heat Pipes Dimensions	ø6mm
Fan Dimension	92 x 92 x 25 mm (3.6 x 3.6 x 1 in)
Fan Speed	800 - 2, 800 RPM (PWM) +/- 10%
	800 - 2, 200 RPM (PWM) +/- 10% (EU Version)
Fan Airflow	15.7 - 54.8 CFM +/- 10%
	15.7 - 43.1 CFM +/- 10% (EU Version)
Fan Air Pressure	0.35 - 4.27mm H2O +/- 10%
	0.35 - 2.63mm H2O +/- 10% (EU Version)
Fan Life Expectancy	40, 000 hours
Fan Noise Level (dB-A)	17 - 35 dBA
	17 - 30 dBA (EU Version)
Bearing Type	Long Life Sleeve Bearing
Connector	4-Pin
Fan Rated Voltage	12 VDC
Fan Rated Current	0.24A
	0.15A (EU Version)

Power Consumption	2.88W
	1.8W (EU Version)
Fan Weight	73g (0.85 lb)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx.co.za/RR-TX3E-28PK-R1-Coolermaster-Hyper-TX3-Evo-CPU-Air-Cooler-p-223445.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx.co.za/terms-of-use.php
Terms of Sale: https://www.comx.co.za/terms-of-sale.php

PDF generated: 2026-11-19 10:54:39.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.