

SYRMXR2B4I

APC Symmetra RM XR Frame w/2 SYBT2 Scalable to 4 220-240V

Product Overview

APC Symmetra RM XR Frame w/2 SYBT2 Scalable to 4 220-240V, Shipping Weight: 165.00(lbs) 75.00(kilos), Shipping Dimensions: 13.50x 23.00x 32.00(in) 34.30x 58.40x 81.30(cent)



Specifications

Features:

Rack Mount

1U rackmountable. Hardware included.

Status Indicator LED's

LED status indicators for each phase and an audible alarm provide immediate failure notification when surge suppression circuitry has been damaged by a heavy strike or surge.

Hot Pluggable Operation

Add or remove servers without having to power off the switch.

Cascading capabilities

Horizontal console port servers can be cascaded to manage up to 1,024 devices.

Intelligent battery management

Maximizes battery performance, life, and reliability through intelligent, precision charging.

Specifications:

© 2015 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	SYRMXR2B4I
--------------	------------

Batteries & Runtime

ComX Computers

Product Specification Sheet

Battery Volt-Amp-Hour Capacity	1224
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	19 inch Battery tray
Expected Battery Life (years)	41703
Included Battery Modules	2
Available Battery Module Slots	2
RBC Quantity	2
Physical	
Net Weight	65.46 KG
Maximum Height	178.00 mm
Maximum Width	483.00 mm
Maximum Depth	640.00 mm
Shipping Weight	75.00 KG
Shipping Width	584.00 mm
Shipping Height	343.00 mm
Shipping Depth	813.00 mm
Rack Height	4U
Color	Black
Environmental	
Operating Environment	0 - 40 degreesC
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-55 - 60 degreesC
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/SYRMXR2B4I-APC-Symmetra-RM-XR-Frame-w-2-SYBT2-Scalable-Buy-p-120991.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-09 06:09:50.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing

ComX Computers

Product Specification Sheet

decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.