

Trinity Mini-G-BK-v3

Aerocool Trinity Mini Black Micro ATX Tower Case

Product Overview

Aerocool Trinity Mini Black tower case - 2x 140mm and 1x 120mm RGB included - Micro ATX - 2x3.5" or 3x 2.5" - 240mm radiator



Specifications

Overview:

Designed with ventilation in mind, this case delivers superior air flow while allowing for viewing of your front LED fans. This high-performance mini tower case comes equipped with a full tempered glass side panel to showcase the inside of your rig. Supports liquid cooling in the front and rear of the case for maximum efficiency cooling.

Features:

- Front panel with air vents delivers superior air flow and ventilation while allowing for viewing of your front LED fans
- Comes equipped with a full tempered side panel to showcase the inside of your rig
- Fan mounts on the PSU shroud support up to two 12cm fans for improved VGA cooling
- Supports liquid cooling in the front and rear of the case
- Supports air cooling in the front, top, and rear of the case
- Dual chamber design for improved ventilation

IMPROVED AIR VENTILATION

Stylish front panel design with built-in air vents delivers increased air flow and ventilation while allowing for viewing of your front LED fans.

FULL TEMPERED GLASS SIDE PANEL

Comes equipped with a full tempered glass side panel to showcase the inside of your rig and put your components on display.

COOLING FOR YOUR GRAPHICS CARD

Fan mounts on the PSU shroud support graphics card cooling: 2 x 120mm fans for superior VGA cooling.

AIR COOLING

Supports air cooling in the front, top, and rear of the case to enhance cooling performance.

- Front: 120mm x 2 or 140mm x 2 (Max.)

ComX Computers

Product Specification Sheet

- Top: 120mm x 2 (Max.)
- Rear: 120mm x 1 (Max.)
- PSU Shroud: 120mm x 2 (Max.)

LIQUID COOLING

Supports liquid cooling in the front and rear of the case for maximum efficiency cooling.

- Front: 120/240mm Radiator (Optional) (for 240mm, supports max length of 240mm and max thickness of 28mm)
- Rear: 120mm Radiator (Optional)

DUAL CHAMBER DESIGN

Built with a dual chamber design to direct heat away from the main chamber for more effective all-around cooling.

BUILT FOR HIGH PERFORMANCE

- Supports Micro-ATX and mini-ITX motherboards
- Supports CPU coolers up to 158mm
- Supports high-end graphics cards up to 297mm (without front radiator)

CONVENIENT ACCESS TO YOUR MEDIA

Quick and easy access to USB 3.0 x 2, USB 2.0 x 1, HD audio and mic ports, and power & reset button.

STORAGE CAPABILITY

Supports up to 2 x 3.5" HDDs (2 x 3.5"/2.5'') and 3 x 2.5" SSDs (1 x 2.5" and 2 x 2.5"/3.5").

Specifications:

© 2025 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	Trinity Mini-G-BK-v3
Model	Trinity Mini
Case Type	Mini Tower
Color	Black
Body Material	SPCC
Front Panel Material	ABS
Steel Thickness	0.5mm
Motherboards	Micro ATX/mini-ITX
Case Dimensions (Internal)	200 x 375 x 300mm (W x H x D)
Case Dimensions (Overall)	206.5 x 385 x 353.4mm (W x H x D)
3.5" Drive Bays	2 Max. (2 x 3.5"/2.5")
2.5" Drive Bays	3 Max. (1 x 2.5" and 2 x 2.5"/3.5")
Expansion Slots	4
GPU Clearance	Supports GPU up to 297mm (without front radiator)
CPU Cooler Clearance	Supports CPU cooler up to 158mm

ComX Computers

Product Specification Sheet

Air Cooling	Front: 120mm x 2 or 140mm x 2 (Max.)
	Top: 120mm x 2 (Max.)
	Rear: 120mm x 1 (Max.)
	PSU Shroud: 120mm x 2 (Max.)
Liquid Cooling	Front: 120/240mm Radiator (Optional)
	(for 240mm, supports max thickness of 28mm)
	Rear: 120mm Radiator (Optional)
I/O Ports	USB3.0 x 2, USB2.0 x 1, HD Audio & Mic.
Internal Cable Management Depth	20.5mm
Power Supply	ATX PSU (Including cables, up to 159mm) (Optional)
EAN Code	Trinity Mini-G-BK-v1: 4710562758610 (includes: 12cm black fan x 1)
	Trinity Mini-G-BK-v2: 4710562758627 (includes: 14cm FRGB fan x 2, 12cm FRGB fan x 1)
	Trinity Mini-G-BK-v3: 4710562758634 (includes: 14cm RGB fan x 2, 12cm RGB fan x 1)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/Trinity-Mini-G-BK-v3-Aerocool-Trinity-Mini-Black-Micro-Buy-p-322063.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-26 07:19:38.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.