

UB-USW-LITE-16-POE

Ubiquiti UniFi PoE Switch Lite 16 Port Gigabit PoE managed Layer 2 Switch

Product Overview

Ubiquiti UniFi PoE Switch Lite 16 Port Gigabit PoE managed Layer 2 Switch, 8 auto-sensing 802.3at PoE + ports, 45W PoE wattage, USW-LITE-16-POE, 16x 10/100/1000 Mbps Ethernet RJ45, 8x PoE+ IEEE 802.3af/at



Specifications

Overview:

UniFi Switch Lite 16 PoE

SKU: USW-Lite-16-POE

The UniFi Switch Lite 16 PoE is a fully managed Layer 2 switch with sixteen Gigabit Ethernet ports for your RJ45 Ethernet devices. Eight ports also offer auto-sensing 802.3at PoE+ that provide up to a total PoE wattage of 45W for UniFi Access Points or other PoE devices.??

Managed and configured by the UniFi Network Controller with UniFi mobile app support, the UniFi Switch Lite 16 PoE offers Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.

Features:

- (16) Gigabit RJ45 ports including (8) 802.3at PoE+
- Managed by UniFi Controller
- 60W power supply
- Wall-mountable (Kit included)

Managed by UniFi Network Controller version: 5.13.5 or higher

Specifications:

© 2020 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	UB-USW-LITE-16-POE
Mechanical	
Dimensions	191.7 x 185 x 43.7 mm
	(7.55 x 7.28 x 1.72")
Weight	1.2 kg
	(2.65 lb)
Hardware	
Total Non-Blocking Line Rate	16 Gbps
Max. Power Consumption	15W
Power Method	Universal AC Input: 100-240VAC
Power Supply	Internal 60W AC/DC Power Supply
Networking Interfaces	(16) 10/100/1000 Mbps Ethernet RJ45
PoE Interfaces	(8) PoE+ IEEE 802.3af/at (Pins 1, 2+, 3, 6-)
Management Interface	Ethernet In-Band
Max PoE+ Wattage per Port by PSE	30W
Modes	SMB Layer 2 PoE Gigabit Ethernet Switch
Operating Temperature	-15 to 40 degrees C (5 to 104 degrees F)
Operating Humidity	10 - 90% Noncondensing

ComX Computers

Product Specification Sheet

Certifications	CE, FCC, IC
LED	
System	(1) Power, Blue/White
	Flashing White: Bootup in Progress
	Flashing Blue: Firmware Upgrading
	Steady White: Factory Defaults, Awaiting Adoption
	Steady Blue: Device is Adopted
Ethernet	Green: 1G, Amber: 10/100 Mbps
PoE	Amber: IEEE 802.3af/at

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/UB-USW-LITE-16-POE-Ubiquiti-UniFi-PoE-Switch-Lite-16-Buy-p-247892.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-12 10:44:33.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.