

# UN-AC-T112-F28

Uniview UNV 2MP HD Fixed IR Mini Turrent Analog Camera with 2.8mm lens

## Product Overview

Uniview UNV 2MP HD fixed IR Mini turrent Analog camera with 2.8mm Lens, One IR illuminator, 20m illumination distance, 1080p Resolution, PAL, NTSC, 2D Digital Noise Reduction, DWDR, 5.5mm Power Interface, BNC supports TVI / AHD / CVI / CVBS, IP67 ingress protection



## Specifications

### Overview:

#### UAC-T112-F28(40)

2MP HD Fixed IR Turret Analog Camera

- 2MP high quality image
- TVI/AHD/CVI/CVBS
- IR-cut filter with auto switch (ICR)
- Supports 180 degrees horizontal flip, 180 degrees vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- 3-Axis

### Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

| Specifications |                |
|----------------|----------------|
| Product Code   | UN-AC-T112-F28 |
| Model          | UAC-T112-F28   |
| Sensor         |                |
| Pixel          | 2MP            |

## ComX Computers

### Product Specification Sheet

|                         |                                                                                  |
|-------------------------|----------------------------------------------------------------------------------|
| Size                    | 1/3"                                                                             |
| Minimum illumination    | 0.02 lux (F2.0, AGC ON)                                                          |
|                         | 0 lux (IR on)                                                                    |
| Lens                    |                                                                                  |
| Lens                    | 2.8mm                                                                            |
| Lens mount              | M12                                                                              |
| Angle of view           | H: 90.5 degrees V: 49.6 degrees D: 109.5 degrees                                 |
| Illuminator             |                                                                                  |
| Illuminator             | One IR illuminator                                                               |
| Illumination distance   | 20m                                                                              |
| Lifetime                | >=60, 000 hours                                                                  |
| Image                   |                                                                                  |
| Resolution              | 1080P: 1920(H) x 1080(V)                                                         |
|                         | 720P: 1280(H) x 720(V)                                                           |
| Frame rate              | TVI/AHD/CVI: 1080P@30fps, 1080P@25fps, 720P@30fps, 720P@25fps                    |
|                         | CVBS: PAL, NTSC                                                                  |
| Shutter time            | PAL: 1/25s-1/50000s                                                              |
|                         | NTSC: 1/30s-1/50000s                                                             |
| Image                   |                                                                                  |
| Exposure mode           | 4 modes: Global (default), BLC, HLC, DWDR                                        |
| Day/Night               | 3 modes: Auto (default), Day, Night                                              |
| Digital noise reduction | 2D                                                                               |
| White balance           | Two modes: Auto (default), Manual                                                |
| WDR                     | DWDR                                                                             |
| Smart IR                | Support                                                                          |
| Flip                    | Supports 180 degrees horizontal flip, 180 degrees vertical flip.                 |
| Interface               |                                                                                  |
| Power                   | 5.5mm power interface                                                            |
| Video output            | BNC, supports TVI/AHD/CVI/CVBS                                                   |
| Operating environment   |                                                                                  |
| Temperature             | -30 degreesC to 60 degreesC(-22 degreesF to 140 degreesF)                        |
| Humidity                | <=95% (RH, non-condensing)                                                       |
| Surge protection        | 4KV                                                                              |
| Ingress protection      | IP67                                                                             |
| General                 |                                                                                  |
| Power                   | DC 12V(+/-25%), with reverse polarity protection and surge protection, Max 2.88W |
| Mount                   | Surface mount (default), optional backbox, wall mount bracket                    |

---

## ComX Computers

### Product Specification Sheet

|                      |                               |
|----------------------|-------------------------------|
| <b>Dimensions</b>    | Ø118mm*96mm (diameter*height) |
| <b>Material</b>      | Plastic                       |
| <b>Weight</b>        | 182g(0.401lb)                 |
| <b>Certification</b> | CB, CE, FCC                   |

## Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

**Product page:** <https://www.comx.co.za/UN-AC-T112-F28-Uniview-UNV-2MP-HD-Fixed-IR-Mini-Turrent-Buy-p-285170.php>

---

*Images and specifications are provided for reference and are subject to change without notice. E&OE.*

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

---

PDF generated: 2026-10-11 15:37:28.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.