

UN-IPC3234SB-ADZK-I0

Uniview UNV Ultra H265 4MP HD LightHunter IR VF dome Network camera with 2.7 ~ 13.5mm lens

Product Overview

Uniview UNV Ultra H265 4MP HD LightHunter IR VF dome Network camera, 1/3" 4.0megapixel Progressive Scan CMOS sensor, 2.7 ~ 13.5mm AF automatic focusing and motorized Zoom Lens, Built-In Mic, 4MP 2688 x 1520 @ 30/25fps, Up to 40m range, Digital defog, Ultra 265 / H.265 / H.264 / MJPEG Video Compression, 2D/3D DNR, Micro SD up to 256GB, 1 / 1 alarm I/O, 1x RJ45 10M/100M Base-TX Ethernet, IP67 ingress protection, IK10 vandal resistant



Specifications

Overview:

IPC3234SB-ADZK-I 0 4MP HD LightHunter IR VF Dome Network Camera

- High quality image with 4MP, 1/3"CMOS sensor
- 4MP (2688*1520)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296) @ 30/25fps; 2MP (1920*1080) @30/25fps;
- Ultra 265, H.265, H.264, MJPEG
- LightHunter technology ensures ultra-high image quality in low illumination environment
- 120dB true WDR technology enables clear image in strong light scene
- Support 9:16 Corridor Mode
- Built-in Mic
- Alarm:1 in/1 out, Audio: 1 in/1 out
- Smart IR, up to 40m (131ft) IR distance
- Supports 256 G Micro SD card
- IK10 vandal resistant
- IP67 protection
- Support PoE power supply

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

ComX Computers

Product Specification Sheet

Product Code	UN-IPC3234SB-ADZK-I0
Item	IPC3234SB-ADZK-I0
Camera	
Sensor	1/3", 4.0megapixel, progressive scan, CMOS
Lens	2.7 ~ 13.5mm, AF automatic focusing and motorized zoom lens
Angle of View (H)	98.26 degrees~ 31.35 degrees
Angle of View (V)	54.76 degrees~ 18.55 degrees
Angle of View (O)	127.74 degrees~36.99 degrees
Adjustment angle	Pan: 0 degrees ~ 355 degrees
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.002Lux (F1.2, AGC ON)
	0Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>56dB
IR Range	Up to 40m (131ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
Defog	Digital Defog
WDR	120dB
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 4MP (2688*1520), Max 30fps, 4MP (2560*1440), Max 30fps, 3MP (2304*1296), Max 30fps, 1080P (1920*1080), Max 30fps
	Sub Stream: 720P (1280*720), Max 30fps, D1 (720*576), Max 30fps, 640*360, Max 30fps, 2CIF(704*288), Max 30fps, CIF(352*288), Max 30fps
	Third Stream: D1 (720*576), Max 30fps, 640*360, Max 30fps, 2CIF(704*288), Max 30fps, CIF(352*288), Max 30fps
Video Bit Rate	128 Kbps~16 Mbps
9:16 Corridor Mode	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support

ComX Computers

Product Specification Sheet

Flip	Normal / Vertical / Horizontal / 180 degrees / 90 degreesClockwise / 90 degreesAnti-clockwise
Dewarping	N/A
HLC	Supported
BLC	Supported
Audio	
Audio Compression	G.711
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR, NAS(NFS)
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Client	EZStation
	EZView
	EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Audio I/O	Input: impedance 35kohm, amplitude 2V [p-p]
	Output: impedance 600ohm, amplitude 2V [p-p]
Alarm I/O	1/1
Built-in Mic	Supported
Network	1 RJ45 10M/100M Base-TX Ethernet
Certifications	
Certifications	CE: EN 60950-1
	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V+/-25%, PoE (IEEE 802.3af)
	Power consumption: Max 7.0W
Dimensions (Ø x H)	Ø148 x 111.3mm (Ø5.8" x 4.4")
Net Weight	0.92kg (2.03lb)
Material	Metal + Plastic

ComX Computers

Product Specification Sheet

Working Environment	-30 degreesC ~ 60 degreesC (-22 degreesF ~ 140 degreesF), Humidity: <=95% RH (non-condensing)
Storage Environment	-30 degreesC ~ 60 degreesC (-22 degreesF ~ 140 degreesF), Humidity: <=95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx.co.za/UN-IPC3234SB-ADZK-I0-Uniview-UNV-Ultra-H265-4MP-HD-Buy-p-260649.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx.co.za/terms-of-sale.php>

PDF generated: 2026-10-06 05:40:50.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.