

# Compuprint 3056/N

The Compuprint 3056 and 3056N are designed to be the ideal solution for administrative applications as well for industrial and logistics environments.

These printers satisfy a wide range of printing solutions thanks to the architectural simplicity of the front form feed and refined printing technology.

Compuprint 3056 and 3056N are suited for printing applications using multipart forms, single sheets, labels and envelopes.



### Value and Features

- 24 pins print-head technology
- 560 cps speed
- Complete and flexible paper path
- Single sheet and fanfold handling
- 1+5 copies capability
- Wide range of connectivity
- Easy to use
- Wide range of barcodes and fonts

### Matching your needs and getting your job done in time

Compuprint 3056 and 3056N are ideal for use in a broad range of industries, from data processing, banking, pharmaceuticals or healthcare, warehouse and logistic, education and public administrations.

These printers in single or multi-user environments print at speeds of up to 560 characters per second in draft mode offering an excellent print quality with clear, crisp output of text and graphics.

### Safe and simple paper management

Thanks to the possibility to choose either front or rear paper feed these printers are the best solution for all types of working environment. Straight feeding enables a wide variety of both single sheet, continuous and multiple copy forms to be managed in a safe and reliable manner.

It is also possible to install both printers a second tractor to improve the productivity.

### For a broad range of connectivity

Compuprint 3056 is available in two different configurations, Parallel/Serial/USB or Parallel/USB/LAN to let the user able the installation on networked environment. The LAN models are provided with a Network Interface Manager which is a software used to manage on-line network dot matrix printers.

|                              |                                                                                                                                                                                                                                                                                    |         |         |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------|
| Printing Technology          | 24 pin - serial dot matrix printers                                                                                                                                                                                                                                                |         |         |
| Printing resolution          | 360 x 180 dpi                                                                                                                                                                                                                                                                      |         |         |
| Printing speed               | Mode                                                                                                                                                                                                                                                                               | 12 cpi  | 10 cpi  |
|                              | HDS                                                                                                                                                                                                                                                                                | 650 cps | 560 cps |
|                              | Draft                                                                                                                                                                                                                                                                              | 520 cps | 480 cps |
|                              | NLQ                                                                                                                                                                                                                                                                                | 288 cps | 240 cps |
|                              | LQ                                                                                                                                                                                                                                                                                 | 144 cps | 120 cps |
| Line Length                  | 136 columns @ 10 cpi                                                                                                                                                                                                                                                               |         |         |
| Paper handling               | Cut sheet: width from 101 to 420 mm / A5, A4, A3 (H/V) - lenght up to 364 mm<br>Continuous form: width from 101 to 406 mm - lenght unlimited<br>Paper thickness: 0,065 to 0.52 mm                                                                                                  |         |         |
| Paper type                   | Cut sheet, Continuous paper, Multi-part forms, Envelopes, postcard, adhesive labels                                                                                                                                                                                                |         |         |
| Paper path                   | Friction feed: rear in top out, front in top out - Tractor feed: rear in top out, front in top out, bottom in top out                                                                                                                                                              |         |         |
| Copies                       | 1 + 5                                                                                                                                                                                                                                                                              |         |         |
| Special functions            | Automatic paper parking, Zero tear-off                                                                                                                                                                                                                                             |         |         |
| Barcodes                     | UPC/A - EAN8 - EAN13 - UPCA/E - Code 39 - Code 128 - 2/5 Interleaved - Postnet                                                                                                                                                                                                     |         |         |
| Character set                | ASCII, Italic, CP437, CP850, CP860, CP863, CP865, CP858, CP737 (437G), CP857, CP1250, CP864, CP1098, CP1256<br>International Character Set: USA, France, Germany, England, Denmark, Sweden, Italy, Spain, Japan, Norway, Denmark 2, Spain 2, Latin America, Korea, Legal           |         |         |
| Resident font                | Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Orator-S, OCR-A, OCR-B                                                                                                                                                                                                |         |         |
| Resident Emulations          | Epson ® LQ-ESC/P, OKI, IBM ProPrinter (PPDS)                                                                                                                                                                                                                                       |         |         |
| Interfaces                   | Centronics, Parallel IEEE 1284 bidirectional - Serial RS232 - USB (Base models)<br>Centronics, Parallel IEEE 1284 bidirectional - USB - Ethernet LAN 10/100 BaseT (N models)<br>Input buffer up to 128 Kbytes; Automatic interface switching; Plug-in & Play (Windows environment) |         |         |
| Drivers                      | Windows 95/98/2000/XP/Vista/Win7/Win8/Win10 - Unix - Linux                                                                                                                                                                                                                         |         |         |
| SW Tool                      | Network Interface Manager - Internal web page                                                                                                                                                                                                                                      |         |         |
| Reliability                  | MTBF: 20.000 hours at 25% Duty Cycle<br>MPVBF: 24 million lines (except print head)                                                                                                                                                                                                |         |         |
| Print Head Life              | 400 million strokes/wire                                                                                                                                                                                                                                                           |         |         |
| Ribbon life                  | up to 10 million characters                                                                                                                                                                                                                                                        |         |         |
| Noise Level                  | <55 dBA                                                                                                                                                                                                                                                                            |         |         |
| Power Supply                 | Tension: 100-240V; Frequency: 50-60Hz                                                                                                                                                                                                                                              |         |         |
| Power consumption            | 75 W Max. (printing), 15 W (standby)                                                                                                                                                                                                                                               |         |         |
| Physical Dimensions & Weight | 623 (W) x 395 (D) x 173 (H) mm - 13 Kg                                                                                                                                                                                                                                             |         |         |



## Compuprint SALES CONTACTS

Italy: (+39) 011 9892 141 -  
Other Countries: (+39) 011 9892 141 -  
Website: [www.compuprint.com](http://www.compuprint.com)  
Email: [sales@compuprint.com](mailto:sales@compuprint.com)



Ordering Information

## Printers and Supplies

|                                           |           |
|-------------------------------------------|-----------|
| Compuprint 3056 Basic Printer (P-S-U)     | PRTN3056  |
| Compuprint 3056 LAN Printer (P-U-N)       | PRTN3056N |
| Compuprint Black Ribbon Cartridges(8 pcs) | PRK3050-8 |

## Options

|                         |          |
|-------------------------|----------|
| Optional second tractor | PRFN3056 |
|-------------------------|----------|

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.  
Copyright © March 2017 Compuprint.