



3.5 HARD DRIVE DATA SHEET

Smart. Safe. Secure.  
Video Optimised and Edge Ready



Seagate® SkyHawk™ AI 18 TB is a video-optimised drive designed for NVRs with artificial intelligence (AI) for edge applications.



#### Best-Fit Applications

- Network video recorders (NVR)
- AI-enabled NVR systems



SKYHAWK  
HEALTH



## Key Advantages

**ImagePerfect™ AI firmware** delivers zero dropped frames while supporting heavier workloads.

**Versatile capabilities** intelligently adapt to the scale of your AI environment, supporting up to 64 HD video streams and 32 AI streams.

**Rescue Data Recovery Services.<sup>2</sup>** SkyHawk AI comes with extra peace of mind for any mechanical, accidental, or natural disaster. With a 95% success rate of in-house recovery, Seagate has your back with a 3-year included Rescue Services plan.

**SkyHawk Health Management** actively helps protect your video storage by focusing on prevention, intervention and recovery options.<sup>1</sup> Included RAID RapidRebuild™ provides 3× faster volume rebuilds.

**Class-Leading Reliability and Dependability** SkyHawk AI drives are rated for 2M hours MTBF and a 550 TB/year workload rate for more than 3x that of standard surveillance hard drives. Backed by a 5-year limited warranty.

**Powerful processing** to welcome workload challenges — SkyHawk AI supports video analysis and recording simultaneously with GPU analytics workloads.

**Enjoy consistent performance** with built-in rotational vibration sensors providing reliable storage for NVR with little lag or downtime.

**Multi-bay support** helps you meet your growing storage demands with up to 16+ bays.

<sup>1</sup> Contact your Seagate sales representative for further information.



| Specifications                                     | 18 TB              | 16 TB              | 12 TB              | 10 TB              | 10 TB              |
|----------------------------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Capacity                                           | 18 TB              | 16 TB              | 12 TB              | 10 TB              | 10 TB              |
| Standard Model Numbers                             | ST18000VE002       | ST16000VE002       | ST12000VE001       | ST10000VE0008      | ST10000VE001       |
| Interface                                          | SATA 6 Gb/s        | SATA 6 Gb/s        | SATA 6 Gb/s        | SATA 6 Gb/s        | SATA 6 Gb/s        |
| Recording Technology                               | CMR                | CMR                | CMR                | CMR                | CMR                |
| Drive Design                                       | Helium             | Helium             | Helium             | Helium             | Air                |
| Features and Performance                           |                    |                    |                    |                    |                    |
| Drive Bays Supported                               | 16+                | 16+                | 16+                | 16+                | 16+                |
| AI Channels                                        | 32                 | 32                 | 32                 | 32                 | 32                 |
| AI Real Time Capture Events/Sec <sup>1,2</sup>     | Up to 120          | Up to 120          | Up to 120          | Up to 120          | Up to 120          |
| AI Real Time Compare Events/Sec <sup>1,2</sup>     | Up to 96           | Up to 96           | Up to 96           | Up to 96           | Up to 96           |
| HD Cameras Supported <sup>3</sup>                  | Up to 64           | Up to 64           | Up to 64           | Up to 64           | Up to 64           |
| RV Sensors                                         | Yes                | Yes                | Yes                | Yes                | Yes                |
| Max. Sustained Transfer Rate OD (MB/s)             | 260MB/s            | 250MB/s            | 250MB/s            | 250MB/s            | 245MB/s            |
| Cache (MB)                                         | 256                | 256                | 256                | 256                | 256                |
| Reliability/Data Integrity                         |                    |                    |                    |                    |                    |
| Tarnish Resistant                                  | Yes                | Yes                | Yes                | Yes                | Yes                |
| Load/Unload Cycles                                 | 600,000            | 600,000            | 600,000            | 600,000            | 600,000            |
| Non-recoverable Read Errors Rate, Max              | 1 per 10E15        | 1 per 10E15        | 1 per 10E15        | 1 per 10E15        | 1 per 10E15        |
| Power-On Hours per year                            | 8,760              | 8,760              | 8,760              | 8,760              | 8,760              |
| Workload Rate Limit (WRL) <sup>4</sup>             | 550                | 550                | 550                | 550                | 550                |
| Mean Time Between Failures (MTBF) (hours)          | 2,000,000 hr       | 2,000,000 hr       | 2,000,000 hr       | 2,000,000 hr       | 2,000,000 hr       |
| Warranty, Limited (years) <sup>5</sup>             | 5                  | 5                  | 5                  | 5                  | 5                  |
| Rescue Data Recovery Services (years) <sup>6</sup> | 3                  | 3                  | 3                  | 3                  | 3                  |
| Power Management                                   |                    |                    |                    |                    |                    |
| Startup Current, Typical (12V, A)                  | 2                  | 2                  | 2                  | 1.8                | 2                  |
| Average Operating Power (W)                        | 8 W                | 8 W                | 8 W                | 6.9 W              | 10.1 W             |
| Idling Average (W)                                 | 5.3 W              | 5.3 W              | 5.3 W              | 4.9 W              | 7.8 W              |
| Standby Mode/Sleep Mode, Typical (W)               | 1.3/1.3            | 1.3/1.3            | 1.3/1.3            | 1.2/1.2            | 1/1                |
| Voltage Tolerance (5 V)                            | ±5%                | ±5%                | ±5%                | ±5%                | ±5%                |
| Voltage Tolerance (12 V)                           | ±10%               | ±10%               | ±10%               | ±10%               | ±10%               |
| Environmental/Temperature                          |                    |                    |                    |                    |                    |
| Operating (Ambient, min °C) <sup>7</sup>           | 0                  | 0                  | 0                  | 0                  | 0                  |
| Operating (drive reported, max °C) <sup>7</sup>    | 65                 | 65                 | 65                 | 65                 | 65                 |
| Non-operating (ambient, min °C)                    | -40                | -40                | -40                | -40                | -40                |
| Physical                                           |                    |                    |                    |                    |                    |
| Height (mm/in, max)                                | 26.11 mm/1.028 in  | 26.11 mm/1.028 in  | 26.11 mm/1.028 in  | 26.11 mm/1.028 in  | 26.11 mm/1.028 in  |
| Width (mm/in, max)                                 | 101.85 mm/4.01 in  | 101.85 mm/4.01 in  | 101.85 mm/4.01 in  | 101.85 mm/4.01 in  | 101.85 mm/4.01 in  |
| Depth (mm/in, max)                                 | 146.99 mm/5.787 in | 146.99 mm/5.787 in | 146.99 mm/5.787 in | 146.99 mm/5.787 in | 146.99 mm/5.787 in |
| Weight (g/lb, typical)                             | 670 g/1.477 lb     | 670 g/1.477 lb     | 670 g/1.477 lb     | 690 g/1.521 lb     | 720 g/1.587 lb     |
| Carton Unit Quantity                               | 20                 | 20                 | 20                 | 20                 | 20                 |
| Cartons per Pallet / Cartons per Layer             | 40/8               | 40/8               | 40/8               | 40/8               | 40/8               |

<sup>1</sup> Events can be human, vehicle, or object capture.

<sup>2</sup> Tested and verified using embedded AI NVR – 64-ch HD recording, 16-ch PB. Average picture size ~250 KB

<sup>3</sup> 1080P, H.265, 25 fps

<sup>4</sup> SkyHawk AI surveillance drives are designed for always-on workloads of 550 TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

<sup>5</sup> Extended warranty options available. Consult your distributor for details.

<sup>6</sup> From May 1, 2020, 3-year Rescue Data Recovery Services plan may be offered in addition to standard warranty. This is offered for selected regions only. Check with reseller on availability.

<sup>7</sup> Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the product.



| Specifications                                     | 8 TB               |
|----------------------------------------------------|--------------------|
| Capacity                                           | 8 TB               |
| Standard Model Numbers                             | ST8000VE001        |
| Interface                                          | SATA 6 Gb/s        |
| Recording Technology                               | CMR                |
| Drive Design                                       | Air                |
| <b>Features and Performance</b>                    |                    |
| Drive Bays Supported                               | 16+                |
| AI Channels                                        | 32                 |
| AI Real Time Capture Events/Sec <sup>1,2</sup>     | Up to 120          |
| AI Real Time Compare Events/Sec <sup>1,2</sup>     | Up to 96           |
| HD Cameras Supported <sup>3</sup>                  | Up to 64           |
| RV Sensors                                         | Yes                |
| Max. Sustained Transfer Rate OD (MB/s)             | 245MB/s            |
| Cache (MB)                                         | 256                |
| <b>Reliability/Data Integrity</b>                  |                    |
| Tarnish Resistant                                  | Yes                |
| Load/Unload Cycles                                 | 600,000            |
| Non-recoverable Read Errors Rate, Max              | 1 per 10E15        |
| Power-On Hours per year                            | 8,760              |
| Workload Rate Limit (WRL) <sup>4</sup>             | 550                |
| Mean Time Between Failures (MTBF) (hours)          | 2,000,000 hr       |
| Warranty, Limited (years) <sup>5</sup>             | 5                  |
| Rescue Data Recovery Services (years) <sup>6</sup> | 3                  |
| <b>Power Management</b>                            |                    |
| Startup Current, Typical (12V, A)                  | 2                  |
| Average Operating Power (W)                        | 10.1 W             |
| Idling Average (W)                                 | 7.8 W              |
| Standby Mode/Sleep Mode, Typical (W)               | 1/1                |
| Voltage Tolerance (5 V)                            | ±5%                |
| Voltage Tolerance (12 V)                           | ±10%               |
| <b>Environmental/Temperature</b>                   |                    |
| Operating (Ambient, min °C) <sup>7</sup>           | 0                  |
| Operating (drive reported, max °C) <sup>7</sup>    | 65                 |
| Non-operating (ambient, min °C)                    | -40                |
| <b>Physical</b>                                    |                    |
| Height (mm/in, max)                                | 26.11 mm/1.028 in  |
| Width (mm/in, max)                                 | 101.85 mm/4.01 in  |
| Depth (mm/in, max)                                 | 146.99 mm/5.787 in |
| Weight (g/lb, typical)                             | 720 g/1.587 lb     |
| Carton Unit Quantity                               | 20                 |
| Cartons per Pallet / Cartons per Layer             | 40/8               |

<sup>1</sup> Events can be human, vehicle, or object capture.

<sup>2</sup> Tested and verified using embedded AI NVR – 64-ch HD recording, 16-ch PB. Average picture size ~250 KB

<sup>3</sup> 1080P, H.265, 25 fps

<sup>4</sup> SkyHawk AI surveillance drives are designed for always-on workloads of 550 TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

<sup>5</sup> Extended warranty options available. Consult your distributor for details.

<sup>6</sup> From May 1, 2020, 3-year Rescue Data Recovery Services plan may be offered in addition to standard warranty. This is offered for selected regions only. Check with reseller on availability.

<sup>7</sup> Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the product.

© 2021 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. ImagePerfect, RAID RapidRebuild, SkyHawk, and the SkyHawk AI logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or Gib, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS1960.12C-2103GB March 2021